



B602BRD ESSENTIAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CyberPower B602BRD surge protector offers vital surge protection for common home and office electronics such as computers and peripherals, home theater equipment, and appliances. With 500 joules of surge protection, the B602BRD prevents power surges and power spikes caused by storms and electrical grid fluctuations from reaching and potentially harming your valuable electronic equipment. The B602BRD has six standard, grounded power outlets and a two-foot braided power cord with a standard grounded plug.

Features of the B602BRD include metal oxide varistor (MOV) technology, an EMI/RFI noise filter, keyhole mounting slots, and impact-resistant casing. This surge suppressor comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

FEATURES

- AC Outlets: 6
- AC Outlet Type: NEMA 5-15R
- Surge Protection: 500 Joules
- Cord Length: 2 ft
- Plug Type: NEMA 5-15P
- Plug Style: Straight
- Power Cord Type: Braided
- Electrical Rating: 125V/15A/60Hz
- Connected Equipment Guarantee: \$25,000
- Warranty: Limited Lifetime



SPECIFICATIONS

| INPUT | |
|-----------------------|--------------|
| Circuit Breaker | 15 A |
| Cord Length | 2 ft (0.6 m) |
| Input Plug Type | NEMA 5-15P |
| Maximum Input Current | 15 A |
| Plug Style | Straight |
| OUTPUT | |
| Outlet Type | 6 NEMA 5-15R |
| Outlets - Total | 6 |

| SURGE PROTECTION & FILTERING | |
|------------------------------|--|
| Clamping Voltage | 800V (H-N) |
| EMI/RFI Filtration | 150 KHz 100 MHz Yes |
| Maximum Surge Current | 15,000 A |
| Maximum Surge Current H-N | 15,000 A |
| Maximum Surge Voltage | 6,000 V |
| Response Time | <1 Nanosecond |
| Surge Suppression (Joules) | 500 J |
| PHYSICAL | |
| Color | White |
| Form Factors Supported | Keyhole (Wall Mount or Under-counter Installation) |
| Material of Construction | Plastic |

B602BRD

ESSENTIAL SURGE PROTECTOR

SPECIFICATIONS CONT.

| DIMENSIONS | |
|--|-------------------------|
| Physical Dimensions - Width/Height/Depth (cm) | 4.55 x 3.81 x 24.79 cm |
| Physical Dimensions - Width/Height/Depth (mm) | 45 x 38 x 248 mm |
| Physical Dimensions - Width/Height/Depth (in.) | 1.79 x 1.5 x 9.76 in. |
| Weight (kg) | 0.24 kg |
| Weight (lbs.) | 0.54 lbs. |
| SHIPPING DIMENSIONS | |
| Shipping Dimensions - Width/Height/Depth (cm) | 8.89 x 31.12 x 3.81 cm |
| Shipping Dimensions - Width/Height/Depth (mm) | 88.9 x 311.15 x 38.1 mm |
| Shipping Dimensions - Width/Height/Depth (in.) | 3.5 x 12.25 x 1.5 in. |
| Shipping Weight (kg) | 0.27 kg |
| Shipping Weight (lbs.) | 0.60 lbs. |

| CERTIFICATIONS | |
|-------------------------------|----------------------------|
| Environmental | RoHS Compliant |
| Safety | UL1363, UL1449 4th Edition |
| WARRANTY | |
| CEG Amount | \$25,000 |
| Connected Equipment Guarantee | Lifetime |
| Product Warranty | Limited Lifetime Warranty |