



# B602RC1 SURGE PROTECTOR

Essentially protect and power your devices with the CyberPower six outlet corded surge strip

Ideal for home and personal use, the CyberPower B602RC1 is designed to provide essential protection and power convenience to personal devices where wall receptacles are a bit distant.

### TYPICAL APPLICATIONS

- Convenient surge protection for home and personal use
- Locations where additional outlets and variable power convenience is needed
- Decentralized power needs within 2 feet of wall receptacle

### FEATURES

- On/Off reset control switch and circuit breaker
- Surge protected
- 6 standard outlets
- 2 foot power cord
- Surge Protection: 500 Joules
- \$25,000 Connected Equipment Guarantee



## SPECIFICATIONS

| INPUT                          |            |
|--------------------------------|------------|
| Voltage                        | 125V       |
| Maximum Wattage                | 1875W      |
| Plug Type                      | NEMA 5-15P |
| Plug Style                     | Grounded   |
| Cord Length (FT)               | 2'         |
| Outlets                        | 6          |
| Outlet Type                    | NEMA 5-15R |
| Outlets - Total                | 6          |
| USB Ports                      | 0          |
| USB Port Voltage               | NA         |
| USB Port Amperage              | NA         |
| ENCLOSURE                      |            |
| Color                          | White      |
| Plastic Type                   | ABS        |
| SURGE PROTECTION AND FILTERING |            |
| Surge Suppression              | 500J       |
| Clamping Voltage               | 800V       |
| Maximum Peak Current           | 15000      |
| Maximum Surge current L-N      | 15000      |

| SURGE PROTECTION AND FILTERING CONT. |                      |
|--------------------------------------|----------------------|
| Maximum Surge current L-G            | 0                    |
| Maximum Surge current G-N            | 0                    |
| Phone RJ11                           | None                 |
| Coax Protection                      | None                 |
| EMI/RFI Filtration                   | None                 |
| Attenuation                          | NA                   |
| PHYSICAL                             |                      |
| Dimensions (WxHxD) (mm)              | 1.77 x 1.38 x 9.65   |
| Weight (lbs.)                        | 0.52                 |
| Case Pack Dimensions (WxHxD) (in.)   | 12.20 x 4.72 x 17.32 |
| Case Pack Weight (lbs)               | 5.55                 |
| CERTIFICATIONS                       |                      |
| Certifications                       | cUL                  |
| ROHS                                 | Yes                  |
| WARRANTY                             |                      |
| Product Warranty                     | Limited Lifetime     |
| Connected Equipment Guarantee        | Lifetime             |
| CEG Amount                           | \$25,000             |