



B704 ESSENTIAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The Essential Surge Protector B704 from CyberPower offers vital surge protection for common home and office devices such as computers and electronics. It prevents spikes in energy caused by storms and electrical power surges from reaching your electronic equipment. The B704 provides 1,200 joules of protection with 7 outlets and a power cord (4 ft.).

Features of the B704 include automatic shutdown, metal oxide varistor (MOV) technology, an EMI/RFI noise filter, keyhole mounting slots, and impact-resistant casing. This surge suppressor comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

FEATURES

- Surge suppression: 1,200 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P
- Plug style: Straight
- Outlet type: 7 NEMA 5-15R
- Power cord: 4 ft
- Model color: White
- EMI/RFI Filtration: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$75,000



SPECIFICATIONS

INPUT

| | |
|-----------------------|--------------|
| Circuit Breaker | 15 A |
| Cord Length | 4 ft (1.2 m) |
| Input Plug Type | NEMA 5-15P |
| Maximum Input Current | 15 A |
| Nominal Input Voltage | 125 VAC |

OUTPUT

| | |
|-----------------|--------------|
| Outlet Type | 7 NEMA 5-15R |
| Outlets - Total | 7 |

SURGE PROTECTION & FILTERING

| | |
|------------------|----------------------|
| Attenuation | 32 dB |
| Clamping Voltage | 500V (H-N, H-G, N-G) |

SURGE PROTECTION & FILTERING - CONT.

| | |
|----------------------------|---------------------------|
| EMI/RFI Filtration | 150 KHz 100 MHz Yes |
| Maximum Surge Current | 60,000 A |
| Maximum Surge Current H-G | 15,000 A |
| Maximum Surge Current H-N | 30,000 A |
| Maximum Surge Current L-G | 15,000 A |
| Maximum Surge Current L-N | 30,000 A |
| Maximum Surge Current N-G | 15,000 A |
| Maximum Surge Voltage | 6,000 V |
| Response Time | <1 Nanosecond |
| Surge Suppression (Joules) | 1,200 J |

B704

ESSENTIAL SURGE PROTECTOR

SPECIFICATIONS CONT.

MANAGEMENT & COMMUNICATIONS

| | |
|----------------|-----------|
| LED Indicators | Protected |
|----------------|-----------|

PHYSICAL

| | |
|--------------------------|--|
| Color | White |
| Form Factor | Strip |
| Form Factors Supported | Keyhole (Wall Mount or Under-counter Installation) |
| Material of Construction | Plastic |
| Safety Covers | Yes |

DIMENSIONS

| | |
|-----------------------------------|------------------------|
| Physical Dimensions - WxHxD (cm) | 4.45 x 3.81 x 27.31 cm |
| Physical Dimensions - WxHxD (mm) | 44 x 38 x 273 mm |
| Physical Dimensions - WxHxD (in.) | 1.75 x 1.5 x 10.75 in. |
| Weight (kg) | 0.37 kg |
| Weight (lb) | 0.81 lbs. |

SHIPPING DIMENSIONS

| | |
|----------------------------------|----------------------------|
| Shipping Dimensions - WxHxD (cm) | 3.84 x 31.12 x 10.52 cm |
| Shipping Dimensions - WxHxD (mm) | 38.35 x 311.15 x 105.16 mm |
| Shipping Dimensions - WxHxD (in) | 1.51 x 12.25 x 4.14 in. |
| Shipping Weight (kg) | 5.78 kg |
| Shipping Weight (lbs.) | 12.75 lbs. |

CERTIFICATIONS

| | |
|---------------|----------------|
| Environmental | RoHS Compliant |
| Safety | cUL |

WARRANTY

| | |
|-------------------------------|---------------------------|
| CEG Amount | \$75,000 |
| Connected Equipment Guarantee | Lifetime |
| Product Warranty | Limited Lifetime Warranty |