



BP36V60ART2U | EXTENDED BATTERY MODULE



Extend battery runtime for UPS systems during power outages.

The CyberPower BP36V60ART2U rack/tower convertible Extended Battery Module (EBM), which extends battery runtimes during power outages, is designed for Smart App Online UPS systems OL1000RTXL2U, OL1000RTXL2UN, OL1500RTXL2U and OL1500RTXL2UN. This EBM takes 2U of rack space and can be installed in a rack or tower configuration to match the UPS form factor. It also has a built-in battery charger, providing Fast Charge Technology to quickly restore the backup power supply to full capacity.

Up to ten EBMs can be added to the UPS, and the module's DC plug-and-play power connectors allow for daisy-chaining additional EBMs to a UPS system. The BP36V60ART2U typically has a UPS charging time of four hours, regardless of whether one or ten EBMS are installed, and comes with a three-year warranty.

ELIGIBLE MODELS

- OL1000RTXL2U
- OL1000RTXL2UN
- OL1500RTXL2U
- OL1500RTXL2UN

TYPICAL APPLICATIONS

- Corporate and Enterprise Servers
- Network and Storage Devices
- Edge Closets
- PBX and VoIP Installations

FEATURES

- Output: 36V/60A
- Typical Recharge Time: 4 hours (0-90%)
- Battery Type & Quantity: 12V/9AH (6)
- Form Factor: Rack/Tower
- Hot Swappable: Yes
- Fast Charge Technology: Yes

SPECIFICATIONS

GENERAL

Amperage	60A
DC Voltage	36 VDC

BATTERY

Built-in Charger	Yes
Battery Type	Sealed Lead-Acid Battery
Battery Quantity	6

BATTERY - CONT.

Replacement Battery Cartridge	(1) RB1290X3R & (1) RB1290X3L
Typical Recharge Time	4 Hours (0-90%)
Expansion Ready (Daisy-Chain)	Yes
Battery Size	12 V / 9 Ah
Hot Swappable	Yes
User Replaceable Battery	Yes

BP36V60ART2U | EXTENDED BATTERY MODULE



SPECIFICATIONS - CONT.

PHYSICAL		ENVIRONMENTAL	
Rack Size	2U	Storage Elevation	0 - 50000 ft (0 - 15239 m)
Mounting Hardware	Included	Operating Temperature	32 - 104 °F (0 - 40 °C)
Enclosure Construction	Steel	Storage Temperature	5 - 113 °F (-15 - 45 °C)
Dimensions (WxHxD) cm	43.18 x 8.89 x 42.93 (cm)	Operating Elevation	0 - 10000 ft (0 - 3048 m)
Dimensions (WxHxD) (in)	17 x 3.5 x 16.9 (in)	Storage Relative Humidity	0 - 95% (non-condensing)
Dimensions (WxHxD) (mm)	432 x 89 x 429 (mm)	Operating Relative Humidity	0 - 90 % (non-condensing)
Weight (kg)	22.95	CERTIFICATIONS	
Weight (lb)	50.6	Environmental	RoHS Compliant
Shipping Dimensions - (WxHxD) (in)	21.5 x 9.75 x 22.5 (in)	Safety	UL1778 CSA C22.2 NO.107.3 FCC Part 15 Class B
Shipping Dimensions - (WxHxD) (mm)	546.1 x 247.65 x 571.5 (mm)	WARRANTY	
Shipping Weight (kg)	29.71	Product Warranty	3 Year Limited Warranty
Shipping Weight (lb)	65.5	Extended 2-Year Warranty	WEXT5YR-BP1