



CP425SLG STANDBY UPS SYSTEM

Offers energy savings, battery backup and surge protection.

The CyberPower Standby CP425SLG uninterruptible power supply (UPS) safeguards a home office PC and other electronics (monitors, printers, scanners, speakers, fax machines, CD/DVD players and iPods) from surges, spikes, sags, brownouts and other power abnormalities. Its composite integrated circuitry offers advanced lightning protection.

This UPS system has patented GreenPower UPS™ High Efficiency circuitry to save on energy costs by reducing energy consumption and heat buildup.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material and workmanship, further protection is offered by a \$75,000 Connected Equipment Guarantee.



TYPICAL APPLICATIONS

- Desktop Computers
- Home Networking/VoIP
- Personal Electronics

FEATURES

- 425 VA/255 W
- Standby Topology
- GreenPower UPS™
- Full-time Surge Protection and Battery Backup
- Audible alarms
- Compact Form Factor
- 8 Outlets/USB Port
- EMI/RFI Filters
- PowerPanel® Personal Edition
- Three-Year Warranty

SPECIFICATIONS

GENERAL	
UPS Topology	Standby
Energy Saving	GreenPower UPS™ High Efficiency
INPUT	
Voltage	96 V-140 V
Frequency	47 Hz - 63 Hz
Circuit Breaker	10 Amp
Plug Type	NEMA 5-15P
Plug STyle	Right Angle, 45° Offset Right
Cord Length	5'

OUTPUT	
VA	425
Watts	255
On Battery Voltage	120 V ± 5%
On Battery Frequency	50/60 Hz ± 1%
On Battery Waveform	Simulated Sine Wave
Outlets - Total	8
Outlets - Type	NEMA 5-15R
Outlets - Battery & Surge Protected	4
Outlets - Surge-Only Protected	4
Outlets - Widely Spaced	4

CP425SLG STANDBY UPS SYSTEM



SPECIFICATIONS CONT.

OUTPUT CONT.

Overload Protection	Internal Circuitry Limiting/ Circuit Breaker
---------------------	---

Transfer Time	4ms
---------------	-----

BATTERY

Runtime at Half Load (min)	7
-------------------------------	---

Runtime at Full Load (min)	2
-------------------------------	---

Battery Type	Sealed Lead Acid
--------------	------------------

Battery Size	12 V/3.6 Ah
--------------	-------------

Battery Quantity	1
------------------	---

User Replaceable	No
------------------	----

Typical Recharge Time	8 Hours
-----------------------	---------

SURGE PROTECTION & FILTERING

Surge Suppression	890 Joules
-------------------	------------

EMI/RFI Filtration	Yes
--------------------	-----

MANAGEMENT & COMMUNICATIONS

HID Compliant USB Port	Yes
------------------------	-----

Serial Port	No
-------------	----

Cable Management	USB Cable
------------------	-----------

LED Indicators	Power On, Wiring Fault
----------------	------------------------

MANAGEMENT & COMMUNICATIONS CONT.

Audible Alarms	On Battery, Low Battery, Overload
----------------	--------------------------------------

Software	PowerPanel® Personal Edition
----------	------------------------------

PHYSICAL

Form Factor	Compact
-------------	---------

Keyhole Mounting Slots	Yes
------------------------	-----

Dimensions (WxHxD) (in.)	9.8 x 5.8 x 3.3
-----------------------------	-----------------

Weight (lbs.)	4.2
---------------	-----

ENVIRONMENTAL

Operating Temperature	32°F to 104°F/0°C to 40°C
-----------------------	---------------------------

Operating Relative Humidity	0%-90% (Non-condensing)
--------------------------------	-------------------------

CERTIFICATIONS

Safety	UL1778, cUL 107.3, FCC DOC Class B
--------	---------------------------------------

Environmental	RoHS Compliant
---------------	----------------

WARRANTY

Product Warranty	Three-Years Limited
------------------	---------------------

Connected Equipment Guarantee	Lifetime
----------------------------------	----------

CEG Amount	\$75,000
------------	----------