



CPBC2200 USB Battery Pack

Power and charge devices from a convenient portable charger.

The CyberPower CPBC2200 USB Battery Pack is a rechargeable, long lasting, lithium-ion battery designed for powering mobile devices including smartphones, MP3 players, cameras, and handheld gaming devices while away from other power sources.

The attached USB charging connector can be used for charging the battery pack itself through any powered USB port. Through the additional USB cable, you can charge your devices anywhere, anytime and enjoy up to 40 hours of extra runtime.

A One-Year Warranty ensures that this product has passed our highest quality standards in design, assembly, material and workmanship.

Typical Applications

- Cameras
- MP3 Players
- Smartphones
- Handheld Gaming Devices

Features

- Rechargeable Battery
- Light Compact Design
- Battery Capacity LED Indicator
- Attached USB Charging Connector
- (1) USB Outlet
- 1-Year Warranty

CPBC2200 USB Battery Pack

Power and charge devices from a convenient portable charger.

| GENERAL | |
|---------------------------------|---------------------------------------|
| Product Type | USB Battery Pack |
| INPUT | |
| Voltage | 5V \pm 5% DC |
| Current | 0.6A |
| Power Source | USB Port |
| Input Connector | USB Type A (Male) with attached cable |
| OUTPUT | |
| USB Charge | 5V \pm 5% |
| USB Charge Port - Total | 1 |
| USB Charging Amperage | 1.0A |
| Output Connector | USB Type A (Female) |
| BATTERY | |
| Battery Capacity | 2200mAh |
| Battery Voltage | 3.7V |
| Recharge Time - Hours (Typical) | 4 |
| PROTECTION FEATURES | |
| Short Circuit | Yes |
| Low Voltage | Yes |
| Over Charging | Yes |
| Over Discharging | Yes |
| Discharge Over Current | Yes |
| Energy Saving Mode | N/A |
| INDICATORS | |
| Power On/Off | N/A |
| Battery Capacity | 1 Green/Red Bar, 2 Green Bars |
| Overload | N/A |
| Battery Failure | N/A |
| PHYSICAL | |
| Color | Black |
| Enclosure Construction | ABS |
| Dimensions (WxHxD) (in.) | 1.7 x 0.9 x 3.4 |
| Weight (lbs.) | 0.16 |
| ENVIRONMENTAL | |
| Operating Temperature | 32°F to 104°F / 0°C to 40°C |
| Storage Temperature | 14°F to 122°F / -10°C to 50°C |
| CERTIFICATIONS | |
| Safety | FCC/CE |
| Environmental | RoHS Compliant |
| WARRANTY | |
| Product Warranty | 1 Year Limited |