

CyberPower

CPUDC1U2000 UNIVERSAL POWER ADAPTER



Your replacement or spare DC adapter for portable electronic equipment.

The CyberPower 2.1 Amp CPUD1U200 Universal Power Adapter substitutes for batteries in portable radios, DVD players, and electronic gaming systems. Use the integrated USB port to charge smartphones, MP3 players, and other USB powered devices while you're traveling. Features include a USB charging port, DC power plug, voltage selector, polarity selector, and a set of seven adapter tips compatible with many electronics. The CPUD1U200 comes with a one-year limited warranty.

TYPICAL APPLICATIONS

- Audio Video
- Handheld Gaming Devices
- Laptop Computers

FEATURES

- Charge type: DC
- Output: 2000mA (3-12 volts)
- USB charge port: 1
- USB output: 2.1 Amp
- DC output (selectable): 3V, 4.5V, 6V, 9V, 12V
- DC power plug: Yes
- Power cord: 5-ft
- Adapter tips: 7
- Dual polarity: Yes
- Voltage selector: Yes
- Warranty: One-Year

SPECIFICATIONS

INPUT	
Cord Length	5 ft. (1.5 m)
Input Connector	DC Plug
Input Plug Type	12VDC Auto Power Port
Plug Style	Automotive
OUTPUT	
Adapter Tips (Qty.)	7
Output Cord Length	5 ft.
Output Power	2000 mA

OUTPUT - CONT.	
Output Voltage (Selectable)	3 VDC, 4.5 VDC, 6 VDC, 9 VDC, 12 VDC
USB Charge Port Amperage	2.1 Amps
USB Charge Port Quantity	1 x Type A
USB Charge Port Voltage	5 VDC
PHYSICAL	
Color	Black
Form Factor	DC Adapter
Material of Construction	Plastic

CPUDC1U2000

UNIVERSAL POWER ADAPTER

SPECIFICATIONS - CONT.

PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	5.33 x 12.19 x 2.79 cm
Physical Dimensions - Width/Height/Depth (mm)	53 x 122 x 28 mm
Physical Dimensions - Width/Height/Depth (in.)	2.1 x 4.8 x 1.1 in.
Weight (kg)	0.12 kg
Weight (lb)	0.26 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	16.51 x 5.72 x 20.96 cm
Shipping Dimensions - Width/Height/Depth (mm)	165.1 x 57.15 x 209.55 mm
Shipping Dimensions - Width/Height/Depth (in.)	6.5 x 2.25 x 8.25 in.
Weight (kg)	6.01 kg
Weight (lb)	13.25 lbs.
ENVIRONMENTAL	
Operating Elevation	0 - 10,000 ft (0 - 3,048 m)
Operating Relative Humidity	0 - 95 % (non-condensing)
Operating Temperature	32 - 95 °F (0 - 35 °C)
Storage Elevation	0 - 50,000 ft (0 - 15,239 m)
Storage Temperature	5 - 113 °F (-15 - 45 °C)
CERTIFICATIONS	
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	1-Year Limited Warranty