

# CyberPower

## CR9U61001 CARBON™ WALL MOUNT ENCLOSURE



Wall mount enclosure safeguards 9U of 19" rack equipment

The CR9U61001 is designed for use in network closets, classrooms and other locations. This wall mount enclosure houses network switches and patch panels up to 22" deep. It includes convenient top panel cable access openings, perforated door and side panels for efficient airflow, adjustable rack angles, and square and threaded mounting holes. The CR9U61001 ships fully assembled for quick deployment, and can be customized with compatible accessories. It is covered by a 5-year limited warranty.

### TYPICAL APPLICATIONS

- Rack Type: Wall Mount Enclosure
- Height: 9U
- Stationary Capacity: 132 lbs
- Max. Mounting Depth: 22.2"
- Mounting Hole Types: Square and Threaded
- Warranty: 5 Years

### FEATURES

- Network Closets
- Retail Locations
- Back Office
- Classrooms

## SPECIFICATIONS

### PHYSICAL

Rack Height	9U
Color	Black RAL 9005 powder coat paint
Door Type	Hex Perforated Metal Door
Rack Angle Mounting Hole Type	Square and #12-24 Mounting Hole
Weight Capacity - stationary load (lbs)	132.3
Weight Capacity - stationary load (kg)	60
Factory Default Mounting Depth (in)	17.2
Factory Default Mounting Depth (mm)	436
Cable Access Opening Dimensions (in)	9.8 x 2.2
Cable Access Opening Dimensions (mm)	250 x 56

### PHYSICAL CONT.

Max. Mounting Depth (in)	22.2
Max. Mounting Depth (mm)	562
Min. Mounting Depth (in)	1.9
Min. Mounting Depth (mm)	47
Dimensions (WxHxD in.)	23.6 x 19.9 x 23.6
Dimensions (WxHxD mm)	600 x 505 x 600
Net Weight (lbs)	41.8
Net Weight (kg)	18.9
Shipping Dimensions - WxHxD (in)	26.18 x 22.44 x 26.18
Shipping Weight (lbs)	48.1
Shipping Weight (kg)	21.8

# CR9U61001 CARBON™ WALL MOUNT ENCLOSURE



## SPECIFICATIONS CONT.

SPECIAL FEATURES	
Numbered Rack Units	Yes
Rolling Casters	Optional
Removable Door and Side Panels	Yes
Reversible Front Door	Yes
Lockable Door and Side Panels	Yes, keyed alike
Ventilation	Perforated Door and Side Panels with Ventilated Top and Bottom
Cable Access	Top and Bottom Openings
PE Grounding Point	Yes

ENVIRONMENTAL	
Protection Class	IP20
CERTIFICATIONS	
Certifications	CE, RoHS
Approvals	DIN41491, DIN41494, EIA/ECA-310-E, IEC 60297-3-100
WARRANTY	
Product Warranty	5 Years Limited