



CSB404MP2 | SURGE PROTECTOR MULTI-PACK

Protect home and office computers, electronics, and home theater equipment

The CyberPower Essential Surge protector CSB404MP2 two-pack offers vital surge protection for common home and office devices such as computers and electronics. The CSB404MP2 includes two units of the CyberPower CSB404 which prevents spikes in energy caused by storms and electrical power surges from reaching electronic equipment. The CSB404 provides 450 joules of protection with four outlets and a four-foot power cord.

Features of the CSB404 include automatic shutdown, metal oxide varistor (MOV) technology, an EMI/RFI noise filter, and impact-resistant casing. This surge suppressor comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

FEATURES

- Surge suppression: 450 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P
- Plug style: Straight
- Outlet type: 4 NEMA 5-15R (surge-protected)
- Power cord: 4 ft
- Model color: Black
- EMI/RFI Filtration: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$25,000



SPECIFICATIONS

| INPUT | |
|-----------------------|----------------|
| Circuit Breaker | 15 A |
| Cord Length | 4 ft (1.2 m) |
| Input Plug Type | NEMA 5-15P |
| Maximum Input Current | 15 A |
| Plug Style | Straight |
| OUTPUT | |
| Outlet Type | 4 x NEMA 5-15R |
| Outlets - Total | 4 |

| SURGE PROTECTION & FILTERING | |
|------------------------------|--------------------------|
| Attenuation | 32 dB |
| Clamping Voltage | 500V (H-N, H-G, N-G) |
| EMI/RFI Filtration | 150 KHz / 100 MHz Yes |
| Maximum Surge Current | 22,500 A |
| Maximum Surge Current H-G | 7,500 A |
| Maximum Surge Current H-N | 7,500 A |
| Maximum Surge Current N-G | 7,500 A |
| Maximum Surge Voltage | 6,000 V |
| Response Time | <1 Nanosecond |
| Surge Suppression (Joules) | 450 J |

CSB404MP2

SURGE PROTECTOR MULTI-PACK

SPECIFICATIONS CONT.

| PHYSICAL | |
|--|--|
| Color | Black |
| Form Factors Supported | Keyhole (Wall Mount or Under-counter Installation) |
| Material of Construction | Plastic |
| PHYSICAL DIMENSIONS | |
| Physical Dimensions - Width/Height/Depth (cm) | 5.0 x 3.51 x 21.44 cm |
| Physical Dimensions - Width/Height/Depth (mm) | 50 x 35 x 214 mm |
| Physical Dimensions - Width/Height/Depth (in.) | 1.97 x 1.38 x 8.44 in. |
| Weight (kg) | 0.41 kg |
| Weight (lb) | 0.91 lbs. |

| SHIPPING DIMENSIONS | |
|--|---------------------------|
| Shipping Dimensions - Width/Height/Depth (cm) | 13.0 x 6.02 x 36.83 cm |
| Shipping Dimensions - Width/Height/Depth (mm) | 130.05 x 60.2 x 368.3 mm |
| Shipping Dimensions - Width/Height/Depth (in.) | 5.12 x 2.37 x 14.5 in. |
| Weight (kg) | 0.45 kg |
| Weight (lb) | 1.00 lbs. |
| CERTIFICATIONS | |
| Environmental | RoHS Compliant |
| Safety | UL1363 |
| WARRANTY | |
| CEG Amount | \$25,000 |
| Connected Equipment Guarantee | Lifetime |
| Product Warranty | Limited Lifetime Warranty |