

CyberPower

CSB806

ESSENTIAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CyberPower Essential Surge Protector CSB806 offers vital surge protection for common home and office devices such as computers and electronics. It prevents spikes in energy caused by storms and electrical power surges from reaching your electronic equipment. The CSB806 provides 1,800 joules of protection, 8 outlets (4 widely-spaced for transformer plugs), a power cord (6 ft.), and a right-angle plug with 45° offset.

Features of the CSB806 include automatic shutdown, metal oxide varistor (MOV) technology, an EMI/RFI noise filter, LED status indicators, keyhole mounting slots, a cord management system, and impact-resistant casing. This surge suppressor comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

FEATURES

- Surge suppression: 1,800 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P
- Plug style: Right-angle 45° offset
- Outlet type: 8 NEMA 5-15R (surge-protected)
- Transformer outlets: 4
- Power cord: 6 ft
- Model color: Black
- EMI/RFI Filtration: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$250,000



SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	6 ft (1.8 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Right Angle - 45° Offset
OUTPUT	
Outlet Type	8 - NEMA 5-15R
Outlets - Total	8
Outlets - Widely Spaced	4

SURGE PROTECTION & FILTERING	
Attenuation	32 dB
Clamping Voltage	400V (H-N, H-G, N-G)
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	90,000 A
Maximum Surge Current H-G	30,000 A
Maximum Surge Current H-N	30,000 A
Maximum Surge Current N-G	30,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	1,800 J

CSB806

ESSENTIAL SURGE PROTECTOR

SPECIFICATIONS CONT.

PHYSICAL	
Color	Black
Material of Construction	Plastic
Safety Covers	Yes
PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	10.01 x 3.81 x 27.15 cm
Physical Dimensions - Width/Height/Depth (mm)	100 x 38 x 272 mm
Physical Dimensions - Width/Height/Depth (in.)	3.94 x 1.5 x 10.69 in.
Weight (kg)	0.41 kg
Weight (lb)	0.90 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	3.18 x 36.83 x 15.24 cm
Shipping Dimensions - Width/Height/Depth (mm)	31.75 x 368.3 x 152.4 mm
Shipping Dimensions - Width/Height/Depth (in)	1.25 x 14.5 x 6.0 in.
Weight (kg)	0.73 kg
Weight (lb)	1.60 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1363
WARRANTY	
CEG Amount	\$250,000
Connected Equipment Guarantee	Lifetime
Product Warranty	Limited Lifetime Warranty