



CSHT1208TNC2 | HOME THEATER SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The Home Theater Surge Protector CSHT1208TNC2 provides 3,150 joules of protection and 12 outlets to safeguard your home theater equipment from damage caused by electrical surges. Data line protection occurs with RJ45 ports for networking and RJ11 ports for telecommunication devices such as phones, faxes, modems, and DSL lines. Gold-plated RG6 coaxial connectors protect cable/satellite TV receivers and broadband modems.

Features of the CSHT1208TNC2 include automatic shutdown, 12 surge-protected outlets (4 widely-spaced to accommodate a transformer plug), a power cord (8 ft.), a right-angle plug with 45° offset, LED status indicators, keyhole mounting slots, impact-resistant casing, metal oxide varistor (MOV) technology, and an EMI/RFI noise filter. This surge suppressor comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Home Theater Equipment
- Cable DSL/Modems
- Personal Computers
- Phone/Fax/Modem
- Cable and Satellite
- Consumer Electronics

FEATURES

- Surge suppression: 3,150 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° offset)
- Outlet type: 12 x NEMA 5-15R (surge-protected)
- Widely-spaced outlets: 4
- Power cord: 8 ft
- Data line protection: Telephone, Coaxial, Network
- Cable/Satellite protection: Yes
- EMI/RFI Filtration: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: **\$500,000**



SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	8 ft (2.4 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15A
Plug Style	Right Angle - 45° Offset

OUTPUT	
Outlet Type	12 NEMA 5-15R
Outlets - Total	12
Outlets - Widely Spaced	4

CSHT1208TNC2

HOME THEATER SURGE PROTECTOR

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING

Attenuation	43 dB
Clamping Voltage	400V (H-N, H-G)
Coax Protection RG6	2-in 2-out
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	150,000 A
Maximum Surge Current H-G	30,000 A
Maximum Surge Current H-N	90,000 A
Maximum Surge Current N-G	30,000 A
Maximum Surge Voltage	6,000 V
Network Protection RJ45	1-In / 1-Out
Phone Protection RJ11	1-In / 2-Out
Response Time	<1 Nanosecond
Surge Suppression (Joules)	3,150 J

PHYSICAL

Color	Black
Cord Management	Yes
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
Keyhole Mounting Slots	Yes
Material of Construction	Plastic
Safety Covers	Yes

DIMENSIONS

Physical Dimensions - WxHxD (cm)	13.34 x 4.22 x 31.5 cm
Physical Dimensions - WxHxD (mm)	133 x 42 x 315 mm
Physical Dimensions - WxHxD (in.)	5.25 x 1.66 x 12.4 in.
Weight (kg)	
Weight (lb)	

SHIPPING DIMENSIONS

Shipping Dimensions - WxHxD (cm)	5.13 x 37.31 x 18.42 cm
Shipping Dimensions - WxHxD (mm)	51.31 x 373.13 x 184.15 mm
Shipping Dimensions - WxHxD (in)	2.02 x 14.69 x 7.25 in.
Shipping Weight (kg)	6.46 kg
Shipping Weight (lbs.)	14.25 lbs.

CERTIFICATIONS

Environmental	RoHS Compliant
Safety	UL1363

WARRANTY

CEG Amount	\$150,000
Connected Equipment Guarantee	Lifetime
Product Warranty	Limited Lifetime