

CyberPower

CSHT706TCG TIER 1 ADVANCED POWER STRIP

Safeguard your equipment from damaging power transients and help lower your electric bill

The Home Theater Surge Protector CSHT706TCG provides 2,250 joules of surge protection and 7 outlets to safeguard your home theater equipment from damage caused by electrical surges. Data line protection occurs with RJ11 ports for telecommunication devices such as phones, faxes, modems, and DSL lines. Gold-plated RG6 coaxial connectors protect cable/satellite TV receivers and broadband modems.

Features of the CSHT706TCG include automatic shutdown, 7 outlets (4 energy-saving, 1 widely-spaced for transformer plugs), a power cord (6 ft.), a right-angle plug with 45° offset, LED status indicators, impact-resistant casing, metal oxide varistor (MOV) technology, and an EMI/RFI noise filter. This surge suppressor comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Consumer Electronics

FEATURES

- Surge suppression: 2,250 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° offset)
- Outlet type: 7 x NEMA 5-15R (surge-protected)
- Energy-saving outlets: 4
- Transformer outlets: 1
- Power cord: 6 ft
- Data line protection: Telephone, Coaxial
- Cable/Satellite protection: Yes
- EMI/RFI Noise Filter: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$175,000



SPECIFICATIONS

INPUT		OUTPUT	
Circuit Breaker	15 A	Outlet Type	7 NEMA 5-15R
Cord Length	6 ft (1.8 m)	Outlets - Energy-saving	4
Input Plug Type	NEMA 5-15P	Outlets - Total	7
Maximum Input Current	15 A	Outlets - Widely-spaced	1
Plug Style	Right Angle - 45° Offset		

CSHT706TCG

TIER 1 ADVANCED POWER STRIP

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING		DIMENSIONS	
Attenuation	43 dB	Physical Dimensions - WxHxD (cm)	7.9 x 3.99 x 30.96 cm
Clamping Voltage	400V (H-N, H-G, N-G)	Physical Dimensions - WxHxD (mm)	79 x 40 x 310 mm
Coax Protection RG6	1 In 1 Out	Physical Dimensions - WxHxD (in.)	3.11 x 1.57 x 12.19 in.
EMI/RFI Filtration	150 KHz 100 MHz Yes	Weight (kg)	
Maximum Surge Current	105,000 A	Weight (lb)	
Maximum Surge Current H-G	30,000 A	SHIPPING DIMENSIONS	
Maximum Surge Current H-N	45,000 A	Shipping Dimensions - WxHxD (cm)	5.49 x 37.47 x 11.43 cm
Maximum Surge Current N-G	30,000 A	Shipping Dimensions - WxHxD (mm)	54.86 x 374.65 x 114.3 mm
Maximum Surge Voltage	6,000 V	Shipping Dimensions - WxHxD (in.)	2.16 x 14.75 x 4.5 in.
Phone Protection RJ11	1-In / 2-Out	Shipping Weight (kg)	0.68 kg
Response Time	<1 Nanosecond	Shipping Weight (lbs.)	1.50 lbs.
Surge Suppression (Joules)	2,250 J	CERTIFICATIONS	
PHYSICAL		Environmental	RoHS Compliant
Color	Black	Safety	UL1363
Cord Management	Yes	WARRANTY	
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)	CEG Amount	\$175,000
Material of Construction	Plastic	Connected Equipment Guarantee	Lifetime
Safety Covers	Yes	Product Warranty	Limited Lifetime Warranty