



CSP600WSU | PROFESSIONAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CyberPower Professional Series CSP600WSU Surge Protector is ideal for Home/Office protection with 1,200 joules, 6 swivel outlets, 2 USB charge ports (2.4 Amp shared), and a convenient wall-tap design. The surge protector is ideal for protecting personal computers, phones/fax/modems, printers, stereos, and other electronics. Its two USB ports are perfect for keeping tablets, smart phones, and other rechargeable electronics ready to use.

The CSP600WSU features six outlets, wall-tap plug, MOV technology to guard the surge protector and connected electronics against line abnormalities and lightning surges, while EMI/RFI filters block unwanted line noise. This surge protector comes with a 1-Year Limited Warranty and a \$75,000 Connected Equipment Guarantee.



TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

FEATURES

- Surge suppression: 1,200 J
- Volts: 125 V
- Plug type: NEMA 5-15P
- Outlet type: 6 NEMA 5-15R (surge-protected)
- USB charge ports: 2
- EMI/RFI Filtration: Yes
- LED indicators: Yes
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$75,000

SPECIFICATIONS

INPUT

| | |
|-----------------------|------------|
| Circuit Breaker | None |
| Cord Length | Wall-tap |
| Input Plug Type | NEMA 5-15P |
| Maximum Input Current | 15 A |
| Plug Style | Wall-tap |

OUTPUT

| | |
|--------------------------|-------------------|
| Outlet Type | 6 NEMA 5-15R |
| Outlets - Total | 6 |
| USB Charge Port | Yes |
| USB Charge Port Amperage | 2.4 Amps (Shared) |
| USB Charge Port Quantity | 2 |
| USB Charge Port Standard | Type A |
| USB Charge Port Type | 2 Type A |
| USB Charge Port Voltage | 5 VDC |

SURGE PROTECTION & FILTERING - CON'T

| | |
|----------------------------|---------------------------|
| Attenuation | 32 dB |
| Clamping Voltage | 500V (H-N, H-G, N-G) |
| Coax Protection RG6 | None |
| EMI/RFI Filtration | 150 KHz 100 MHz Yes |
| Maximum Surge Current | 60,000 A |
| Maximum Surge Current H-G | 15,000 A |
| Maximum Surge Current H-N | 30,000 A |
| Maximum Surge Current N-G | 15,000 A |
| Maximum Surge Voltage | 6,000 V |
| Response Time | <1 Nanosecond |
| Surge Suppression (Joules) | 1,200 J |

CSP600WSU

PROFESSIONAL SURGE PROTECTOR

SPECIFICATIONS CONT.

| PHYSICAL | |
|-----------------------------------|----------------------------|
| Color | Black |
| Form Factors Supported | Direct plug |
| Material of Construction | Plastic |
| DIMENSIONS | |
| Physical Dimensions - WxHxD (cm) | 10.67 x 16.26 x 6.35 cm |
| Physical Dimensions - WxHxD (mm) | 107 x 163 x 64 mm |
| Physical Dimensions - WxHxD (in.) | 4.2 x 6.4 x 2.5 in. |
| Weight (kg) | 0.40 kg |
| Weight (lb) | 0.88 lbs. |
| SHIPPING DIMENSIONS | |
| Shipping Dimensions - WxHxD (cm) | 19.2 x 6.22 x 10.72 cm |
| Shipping Dimensions - WxHxD (mm) | 192.02 x 62.23 x 107.19 mm |
| Shipping Dimensions - WxHxD (in) | 7.56 x 2.45 x 4.22 in. |
| Shipping Weight (kg) | 0.45 kg |
| Shipping Weight (lbs.) | 1.00 lbs. |

| CERTIFICATIONS | |
|-------------------------------|------------------|
| Environmental | RoHS Compliant |
| Safety | UL1363 UL498A |
| WARRANTY | |
| CEG Amount Value | \$75,000 |
| Connected Equipment Guarantee | Lifetime |
| Product Warranty | 1-Year Limited |