### **CyberPower**

# CSP604T PROFESSIONAL SURGE PROTECTOR

### Protect home and office computers, electronics, and home theater equipment

The Professional Surge Protector CSP604T from CyberPower offers vital surge suppression for common home and office devices such as computers and electronics. It prevents spikes in energy caused by storms and electrical power surges and is ideal for safeguarding personal computers, phones/faxes/modems, and other consumer electronics. The CSP604T provides 1,350 joules of protection and 6 surge-protected outlets. Data line protection occurs with RJ11 ports for telecommunication devices (phones, faxes, modems, and DSL lines).

Features of the CSP604T include automatic shutdown, data line protection, power cord (4 ft.), right-angle plug with 45° off-set, impact-resistant casing, metal oxide varistor (MOV) technology, and an EMI/RFI noise filter. The CSP604T comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.

#### TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

#### **FEATURES**

- Surge suppression: 1,350 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° off-set)
- Outlet type: 6 NEMA 5-15R (surge-protected)
- Power cord: 4 ft.
- · Color: Black
- Data line protection: Telephone, DSL, Fax
- EMI/RFI Filtration: Yes
- · Warranty: Limited lifetime
- Connected Equipment Guarantee: \$75,000



#### **SPECIFICATIONS**

INPUT		
Circuit Breaker	15 A	
Cord Length	4 ft (1.2 m)	
Input Plug Type	NEMA 5-15P	
Maximum Input Current	15 A	
Plug Style	Right Angle - 45° Offset	
OUTPUT		
Outlet Type	6 - NEMA 5-15R	
Outlets - Total	6	
USB Charge Port	No	
USB Charge Port Amperage	None	

SURGE PROTECTION & FILTERING	
Attenuation	43 dB
Clamping Voltage	400V (H-N, H-G, N-G)
Coax Protection RG6	None
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	60,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	30,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Phone Protection RJ11	1-In / 1-Out
Response Time	<1 Nanosecond
Surge Suppression (Joules)	1,350 J

## CSP604T PROFESSIONAL SURGE PROTECTOR

### **SPECIFICATIONS CONT.**

PHYSICAL		
Color	Black	
Form Factors Supported	Horizontal Mount in Variety of Other Applications	
Material of Construction	Plastic	
PHYSICAL DIMENSIONS		
Physical Dimensions - WxHxD (cm)	4.57 x 3.05 x 21.34 cm	
Physical Dimensions - WxHxD (mm)	46 x 30 x 213 mm	
Physical Dimensions - WxHxD (in.)	1.8 x 1.2 x 8.4 in.	
Weight (kg)	0.32 kg	
Weight (lb)	0.70 lbs.	
SHIPPING DIMENSIONS		
Shipping Dimensions - WxHxD (cm)	34.62 x 5.59 x 9.22 cm	
Shipping Dimensions - WxHxD (mm)	346.2 x 55.88 x 92.2 mm	
Shipping Dimensions - WxHxD (in)	13.63 x 2.2 x 3.63 in.	
Weight (kg)	0.45 kg	
Weight (lb)	1.00 lbs.	

CERTIFICATIONS		
Environmental	RoHS Compliant	
Safety	UL 1363	
WARRANTY		
CEG Amount	\$75,000	
Connected Equipment Guarantee	Lifetime	
Product Warranty	Limited Lifetime Warranty	