



CSP606U42A | PROFESSIONAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CSP606U42A Professional Surge Protector from CyberPower offers vital surge suppression for common home and office devices such as computers and electronics. It is designed to provide maximum protection and convenience to a number of devices where wall receptacles are out of reach. The CSP606U42A prevents damaging spikes in energy caused by storms and electrical power from reaching your electronic equipment. It provides 900 joules of protection, 6 outlets (1 widely-spaced for a transformer plug), 2 USB charging ports, and a low profile right-angle, 6-foot braided power cord. Features of the CSP606U42A include safe-fail notification, Microdot LED protected indicator light, and a 15A Power Breaker Switch. The two USB charging ports with 4.2-amp total output are located at the end of the Professional Surge Protector, offering the best possible reach.

TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

FEATURES

- Surge suppression: 900 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° offset)
- Outlet type: 6 x NEMA 5-15R
- USB charge ports: 2
- Power cord: 6 ft
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$75,000



SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	6 ft (1.8 m)
Input Plug Type	NEMA 5-15P
Input Voltage	125 VAC
Maximum Input Current	15 A
Plug Style	Right Angle - 45° Offset
OUTPUT	
Outlet Type	6 NEMA 5-15R
Outlets - Total	6
USB Charge Port	Yes
USB Charge Port Amperage	4.2 Amps (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	2 Type A
USB Charge Port Voltage	5 VDC

SURGE PROTECTION & FILTERING - CON'T	
Clamping Voltage	500V (H-N, H-G, N-G)
Coax Protection RG6	None
EMI/RFI Filtration	No
Maximum Surge Current	45,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	15,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	900 J

CSP606U42A

PROFESSIONAL SURGE PROTECTOR

SPECIFICATIONS CONT.

PHYSICAL	
Color	White
Form Factors Supported	Horizontal Mount in Variety of Other Applications
Keyhole Mounting Slots	Yes
Material of Construction	Plastic
DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	4.57 x 4.75 x 32.99 cm
Physical Dimensions - Width/Height/Depth (mm)	46 x 47 x 330 mm
Physical Dimensions - Width/Height/Depth (in.)	1.8 x 1.87 x 12.99 in.
Weight (kg)	0.56 kg
Weight (lb)	1.23 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	36.83 x 5.08 x 12.07 cm
Shipping Dimensions - Width/Height/Depth (mm)	368.3 x 50.8 x 120.65 mm
Shipping Dimensions - Width/Height/Depth (in.)	14.5 x 2.0 x 4.75 in.
Shipping Weight (kg)	0.68 kg
Shipping Weight (lbs.)	1.50 lbs.

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1363 UL1310 UL1449 FCC DOE VI
WARRANTY	
CEG Amount Value	\$75,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited