



HT1206UC2 | PREMIUM SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CyberPower Premium Surge Protector HT1206UC2 is ideal for the home, office, or home theater because it is designed to provide maximum protection and convenience to a number of devices where wall receptacles are out of reach. The Premium Surge Protector prevents damaging spikes in energy caused by storms and electrical power from reaching your electronic equipment. The HT1206UC2 provides 4,860 joules of protection, 12 outlets (6 widely-spaced for transformer plugs), 4 USB charging ports, and a right-angle, 6-foot braided power cord.

Features of the HT1206UC2 include safe-fail notification and fireproof technology. This surge suppressor comes with a One-Year Limited warranty and a connected equipment guarantee.

TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

FEATURES

- Surge suppression: 4,860 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° offset)
- Outlet type: 12 x NEMA 5-15R (surge-protected)
- Transformer outlets: 6
- Power cord: 6 ft.
- Data line protection: Coaxial, Network
- Cable/Satellite protection: Yes
- EMI/RFI Filtration: Yes
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$1,000,000



SPECIFICATIONS

INPUT

Circuit Breaker	15 A
Cord Length	6 ft (1.8 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15A

OUTPUT

Outlet Type	12 NEMA 5-15R
Outlets - Total	12

OUTPUT - CONT.

Outlets - Widely Spaced	6
USB Charge Port	Yes
USB Charge Port Amperage	4.8 Amps (Shared)
USB Charge Port Quantity	4
USB Charge Port Type	Type A
USB Charge Port Voltage	5 VDC

HT1206UC2

PREMIUM SURGE PROTECTOR

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING

Attenuation	43 dB
Clamping Voltage	500V (H-N, H-G, N-G)
Coax Protection RG6	2-in 2-out Tin
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	135,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	105,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Network Protection RJ45	1-in / 1-out
Response Time	<1 Nanosecond
Surge Suppression (Joules)	4,860 J

MANAGEMENT & COMMUNICATIONS

LED Indicators	Clean Power Ground LED
----------------	---------------------------

PHYSICAL

Color	Black
Form Factor	Strip
Form Factors Supported	Horizontal Mount in Variety of Other Applications
Material of Construction	Plastic
Safety Covers	No

DIMENSIONS

Physical Dimensions - WxHxD (cm)	13.41 x 3.66 x 32.72 cm
Physical Dimensions - WxHxD (mm)	134 x 37 x 327 mm
Physical Dimensions - WxHxD (in.)	5.28 x 1.44 x 12.88 in.
Weight (kg)	0.97 kg
Weight (lb)	2.13 lbs.

SHIPPING DIMENSIONS

Shipping Dimensions - WxHxD (cm)	44.91 x 5.89 x 24.79 cm
Shipping Dimensions - WxHxD (mm)	449.07 x 58.93 x 247.9 mm
Shipping Dimensions - WxHxD (in)	17.68 x 2.32 x 9.76 in.
Shipping Weight (kg)	1.30 kg
Shipping Weight (lbs.)	2.87 lbs.

CERTIFICATIONS

Environmental	RoHS Compliant
Safety	UUL1363 UL1310 UL1449 3rd Edition cUL FCC DOE6

WARRANTY

CEG Amount	\$1,000,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited