



# HT705GR

## TIER 2 ADVANCED POWER STRIP



Energy-savvy surge protector that economizes standby power for electronics.

Save money and energy with the HT705GR, an advanced power strip (APS) from CyberPower. With seven surge protected outlets (five energy-saving + two always-on) and an automatic infrared sensor, this power-savvy model protects home theater equipment and other electronics. Designed to meet the needs of energy-conscious consumers, this APS reduces the standby power of connected devices.

The HT705GR is controlled by an infrared smart sensor and five adjustable automatic energy-saving outlets that supply power to high-demand equipment such as HDTVs, Blu-ray players, audio receivers, soundbars and streaming media players. The smart infrared sensor reduces energy consumption by shutting down all home theater devices when a remote has not been used for a selected period of time (1 or 2 hours). This device utilizes both physical IR filtering strategies and RMS power sensing with Smart Dynamic Thresholding Capabilities to maximize compatibility and savings.

This APS features a power switch with integrated 15-amp circuit breaker, easy-reach smart sensor cable, LED indicators and EMI/RFI noise filters. It is backed by a Limited Lifetime Warranty and a \$100,000 Connected Equipment Guarantee.

### FEATURES

- Surge suppression: 1500 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° off-set)
- Outlet type: 7 x NEMA 5-15R
- Energy-saving outlets: 5
- Transformer outlets: 2
- EMI/RFI Filtration: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$100,000

### SPECIFICATIONS

INPUT	
Circuit Breaker	15A
Cord Length	5 ft (1.5 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15A
Plug Style	Right Angle, 45° Offset Right

OUTPUT	
Outlet Type	7 x NEMA 5-15R
Outlets - Always-On	2
Outlets - Energy Saving	5
Outlets - Widely-Spaced	2
Outlets - Total	7
Standby Power Consumption	1 W

HT705GR

TIER 2 ADVANCED POWER STRIP



SPECIFICATIONS - CONT.

SURGE PROTECTION & FILTERING	
Attenuation	43dB
Clamping Voltage	500V (H-N, H-G, N-G)
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	60,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	30,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6000 V
Response Time	<1 Nanosecond
Surge Suppression	1500 Joules
MANAGEMENT & COMMUNICATIONS	
LED Indicators	Protected (green) Energy Savings (green) Grounded (green)
SMART SENSOR	
Cord Length	8 ft
Shutdown Timer	15 Minute Notification
Smart Sensor Timer	1 or 2 Hours
Energy Saving	Yes, IR Remote Controlled
PHYSICAL	
Color	Black
Form Factors Supported	Horizontal Mount in Variety of Other Applications
Keyhole Mounting Slots	Yes
Material of Construction	Plastic
Safety Covers	Yes

DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	6.2 x 3.71 x 37.01 cm
Physical Dimensions - Width/Height/Depth (mm)	62 x 37 x 370 mm
Physical Dimensions - Width/Height/Depth (in.)	2.44 x 1.46 x 14.57 in.
Weight (kg)	0.51 kg
Weight (lb)	1.12 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	4.45 x 40.97 x 15.57 cm
Shipping Dimensions - Width/Height/Depth (mm)	44.45 x 409.7 x 155.7 mm
Shipping Dimensions - Width/Height/Depth (in)	1.75 x 16.13 x 6.13 in.
Weight (kg)	9.98 kg
Weight (lb)	22.0 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1363
WARRANTY	
CEG Amount	\$100,000
Connected Equipment Guarantee	Lifetime
Product Warranty	Limited Lifetime Warranty