



HT706UC HOME THEATER SURGE PROTECTION

Protect home theater equipment, home and office computers, and other electronics

Your home entertainment system, gaming gear and devices deserve 24/7 protection. Safeguard valuable electronics against voltage spikes and lightning-induced surges with advanced power protection. Loaded with features like fireproof and safe-fail technology, this surge protector guarantees your home and equipment stay safe. USB charging ports, network line protection, kink-resistant cord and a sleek design make it perfect for all your home entertainment needs.

TYPICAL APPLICATIONS

- Home Theater Equipment
- Cable DSL/Modems
- Personal Computers
- Phone/Fax/Modem
- Cable and Satellite
- Consumer Electronics

FEATURES

- Surge suppression: 2280 J
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° offset)
- Outlet type: 7 x NEMA 5-15R (surge-protected)
- USB Charge Ports: 2 (4.8 A)
- Transformer outlets: 1
- Power cord: 6 ft.
- EMI/RFI Filtration: Yes
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$300,000



SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	6 ft (1.8 m)
Input Plug Type	NEMA 5-15P
Input Voltage Range	100 - 125 VAC
Maximum Input Current	15 A
Plug Style	Right Angle - 45° Offset
Switch	Non-Lighted On/Off - Reset

OUTPUT	
Outlet Type	7 NEMA 5-15R
Outlets - Total	7
Outlets - Widely Spaced	1
USB Charge Port	Yes
USB Charge Port Amperage	4.8 Amps (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	2 x Type A
USB Charge Port Voltage	5 VDC

HT706UC

HOME THEATER SURGE PROTECTION

SPECIFICATIONS - CONT.

SURGE PROTECTION & FILTERING	
Attenuation	43 dB
Clamping Voltage	500V (H-N, H-G, N-G)
Coax Protection RG6	1 In 1 Out Tin
EMI/RFI Filtration	Yes
Maximum Surge Current	75,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	45,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	2280 J
PHYSICAL	
Color	Black
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
Keyhole Mounting Slots	Yes
Material of Construction	Plastic
Safety Covers	No

DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	6.4 x 3.15 x 40.13 cm
Physical Dimensions - Width/Height/Depth (mm)	64 x 31 x 401 mm
Physical Dimensions - Width/Height/Depth (in.)	2.52 x 1.24 x 15.8 in.
Weight (kg)	0.70 kg
Weight (lb)	1.55 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	13.49 x 45.29 x 4.6 cm
Shipping Dimensions - Width/Height/Depth (mm)	134.87 x 452.88 x 45.97 mm
Shipping Dimensions - Width/Height/Depth (in)	5.31 x 17.83 x 1.81 in.
Weight (kg)	0.80 kg
Weight (lb)	1.76 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL498A UL1449 3rd Edition cUL DoE VI NRCan FCC ICES-003
WARRANTY	
CEG Amount	\$300,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited Warranty