

# CyberPower

## HT806TC SURGE PROTECTOR

Centralize, protect and power a variety of devices with the CyberPower eight outlet corded surge solution with additional DSL and Coax protection

Ideal for home, office or theater, the CyberPower HT806U is designed to provide maximum protection and power convenience to a volume of devices where wall receptacles are out of reach and corded transformers accommodation is needed.

### TYPICAL APPLICATIONS

- Maximum surge protection for home, office and theater

### FEATURES

- On/Off reset control switch and circuit breaker
- 8 outlets with safety covers
- One in/out coax protected line
- One in/out/out DSL protected line



## SPECIFICATIONS

INPUT	
Voltage	125 V
Switch	Non-Lighted On/Off - Reset
Plug Type	NEMA 5-15P
Plug Style	Right Angle 45°, 14AWG 60°C 70P
Circuit Breaker	Resettable 15A
Cord Length	6 ft
OUTPUT	
Outlet Type	NEMA 5-15R
Outlets - Total	8 (4 standard, 4 wide-spaced)
PHYSICAL	
Dimensions (WxHxD)(in.)	10.75 x 3.82 x 1.3
Weight (lbs.)	1.49
Case Pack Dimensions (WxHxD)(in.)	13.9 x 11.42 x 6.60
Case Pack Weight (lbs)	10.93
CERTIFICATIONS	
Safety	UL1449 3rd Edition
Environmental	RoHS Compliant

SURGE PROTECTION & FILTERING	
Surge Suppression	3,000 joules
Maximum Surge Current	150,000 amps
Maximum Surge Current H-N	90,000 amps
Maximum Surge Current H-G/N-G	30,000 amps
Clamping Voltage H-N	330V
Clamping Voltage H-G/N-G	500V
Response Time	< 1 nanosecond
EMI/RFI Filtration	150 kHz - 100 MHz
Attenuation	Up to 32dB
Communication Protection	RJ11 1-In / 2-Out
WARRANTY	
Product Warranty	Limited Lifetime
Connected Equipment Guarantee	Lifetime
CEG Amount	\$250,000