



HT812TC

HOME THEATER SURGE PROTECTION

Protect home and office computers, electronics, and home theater equipment

The Home Theater Surge Protector HT812TC provides 4,350 joules of protection and 8 outlets to safeguard your home theater equipment from damage caused by electrical surges. Data line protection occurs with RJ11 ports for telecommunication devices such as phones, faxes, modems, and DSL lines. Gold-plated RG6 coaxial connectors protect cable/satellite TV receivers and modems.

Features of the HT812TC include automatic shutdown, 8 surge-protected outlets (4 widely spaced to accommodate a transformer plug), a power cord (12 ft.), a right-angle plug with 45° offset, LED status indicators, keyhole mounting slots, impact-resistant casing, metal oxide varistor (MOV) technology, and an EMI/RFI noise filter. This surge suppressor comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Home Theater Equipment
- Cable DSL/Modems
- Personal Computers
- Phone/Fax/Modem
- Cable and Satellite
- Consumer Electronics

FEATURES

- Surge suppression: 4,350 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° offset)
- Outlet type: 8 x NEMA 5-15R (surge-protected)
- Transformer outlets: 4
- Power cord: 12 ft
- Data line protection: Telephone, Coaxial
- Cable/Satellite protection: Yes
- EMI/RFI Filtration: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$350,000



SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	12 ft (3.7 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Right Angle - 45° Offset

OUTPUT	
Outlet Type	8 - NEMA 5-15R
Outlets - Total	8
Outlets - Widely-Spaced	4
USB Charge Port	No

HT812TC

HOME THEATER SURGE PROTECTION

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING

Attenuation	58 dB
Clamping Voltage	500V (H-N, H-G, N-G)
Coax Protection RG6	1 in 1 out
EMI/RFI Filtration	150 KHz - 100 MHz
Maximum Surge Current	150,000 A
Maximum Surge Current H-G	30,000 A
Maximum Surge Current H-N	90,000 A
Maximum Surge Current N-G	30,000 A
Maximum Surge Voltage	6,000 V
Network Protection RJ45	1 in / 1 out
Response Time	<1 Nanosecond
Surge Suppression (Joules)	4,350 J

PHYSICAL

Color	Black
Keyhole Mounting Slots	Yes
Material of Construction	Plastic
Safety Covers	Yes

DIMENSIONS

Physical Dimensions - WxHxD (cm)	10.01 x 3.71 x 28.07 cm
Physical Dimensions - WxHxD (mm)	1100 x 37 x 281 mm
Physical Dimensions - WxHxD (in.)	3.94 x 1.46 x 11.05 in.
Weight (kg)	0.91 kg
Weight (lb)	2.00 lbs.

SHIPPING DIMENSIONS

Shipping Dimensions - WxHxD (cm)	17.15 x 5.38 x 34.933 cm
Shipping Dimensions - WxHxD (mm)	171.45 x 53.85 x 349.25 mm
Shipping Dimensions - WxHxD (in)	6.75 x 2.12 x 13.75 in.
Shipping Weight (kg)	1.05 kg
Shipping Weight (lbs.)	2.32 lbs.

CERTIFICATIONS

Environmental	RoHS Compliant
Safety	UL1363 UL1449 4th Edition

WARRANTY

CEG Amount	\$350,000
Connected Equipment Guarantee	Lifetime
Product Warranty	Limited Lifetime