



LX1500GU Battery Backup

Offers significant energy savings, battery backup and surge protection.

A mini-tower Battery Backup/UPS with line interactive topology, the CyberPower Intelligent LCD LX1500GU provides battery power and surge protection for desktop computers, workstations, networking devices, and home entertainment systems.

Two USB 2.1A charging ports provide charging power for portable devices such as tablets, mobile phones, MP3 players, and cameras.

This UPS is ENERGY STAR® qualified with patented GreenPower UPS™ Bypass circuitry to save on energy costs by reducing energy consumption and heat buildup.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material or workmanship and further protection is offered by a \$500,000 Connected Equipment Guarantee.

Typical Applications

- Desktop Computers
- Home Networking/VoIP
- Personal Electronics
- Home Theater Devices

Features

- 1500VA / 900W
- Line-Interactive Topology
- AVR & GreenPower UPS™
- Multifunction LCD Panel
- USB 2.1A Charging Ports
- RJ11/RJ45 and Coax Protection
- Mini-Tower Form Factor
- 10 Outlets / USB Port
- EMI/RFI Filters
- PowerPanel® Personal Edition

LX1500GU Battery Backup

Offers significant energy savings, battery backup and surge protection.

GENERAL	
UPS Topology	Line Interactive
Energy Saving	GreenPower UPS™ Bypass Technology
ENERGY STAR® Qualified	Yes
INPUT	
Voltage	90Vac - 140Vac
Automatic Voltage Regulation	Yes (Single Boost)
Frequency	60Hz ± 3Hz
Circuit Breaker	15 Amp
Plug Type	NEMA 5-15P
Plug Style	Right Angle, 45° Offset Right
Cord Length	6'
OUTPUT	
VA	1,500
Watts	900
On Battery Voltage	120Vac ± 5%
On Battery Frequency	60Hz ± 1%
On Battery Waveform	Simulated Sine Wave
Outlets - Total	10
Outlet Type	NEMA 5-15R
Outlets - Battery & Surge Protected	5
Outlets - Surge-Only Protected	5
Outlets - Widely Spaced	2
USB Charge Port - Total	2
USB Charging Amperage	2.1A (shared)
Overload Protection	Internal circuitry limiting / circuit breaker
BATTERY	
Runtime at Half Load (min)	13
Runtime at Full Load (min)	2
Battery Type	Sealed Lead-Acid
Battery Size	12V/9AH
Battery Quantity	2
User Replaceable	Yes
Typical Recharge Time	8 Hours
SURGE PROTECTION & FILTERING	
Surge Suppression	890 Joules
Phone RJ11 / Ethernet RJ45	1-In, 1-Out (Combo)
Coax Protection RG6	1-In, 1-Out
EMI/RFI Filtration	Yes

MANAGEMENT & COMMUNICATIONS	
Multifunction LCD Panel	Yes
USB Port	Yes
HID Compliant USB Port	Yes
Management Cable	USB Cable
LED Indicators	Power On, Wiring Fault
Audible Alarms	On Battery, Low Battery, Overload, Fault
Software	PowerPanel® Personal Edition
PHYSICAL	
Dimensions (WxHxD) (in.)	3.9 x 9.8 x 13.7
Weight (lbs.)	25.0
Weight (kg.)	11.3
ENVIRONMENTAL	
Operating Temperature	32 °F to 104 °F / 0 °C to 40 °C
Operating Humidity	0% - 90% non-condensing
CERTIFICATIONS	
Safety	UL1778, cUL, FCC DOC Class B
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	3 Years Limited
Connected Equipment Guarantee	Lifetime
CEG Amount	\$500,000