

## MP1075WS MULTI PACK SOLUTIONS

Protect home and office computers, electronics, and home theater equipment

The MP1075WS USB and Surge 2 Pack safeguards common home and office devices, such as computers and electronics, by absorbing spikes in energy caused by storms and electrical power surges. Both units in the 2 pack provide 500 joules of surge protection. The surge protector strip has 4 surge protected AC outlets, while the wall tap has 6 surge protected outlets. Both units also have two USB-A ports to give the ability to charge mobile, USB enabled devices, EMI/RFI noise filtering, impact-resistant casings, and an integrated device shelf on top of the wall tap which serves as a charging cradle.

These models feature metal oxide varistor (MOV) technology and come with Limited Lifetime Warranties and Connected Equipment Guarantees.

### TYPICAL APPLICATIONS

- Desktop Computers
- Personal Electronics
- Routers & Modems



## SPECIFICATIONS

|                                       | P403URC1          | P600WUHD                   |
|---------------------------------------|-------------------|----------------------------|
| <b>OUTLETS</b>                        |                   |                            |
| Total                                 | 4 (NEMA 5-15R)    | 6 (NEMA 5-15R)             |
| <b>USB</b>                            |                   |                            |
| Charging Ports                        | 2 @ 2.4A (shared) | 2 @ 3.4A (shared)          |
| <b>POWER CORD</b>                     |                   |                            |
| Length (Exposed ft.)                  | 3' Standard       | N.A. - Wall Tap            |
| Plug Type                             | 45° Offset Right  | Three Prong Direct Plug-in |
| <b>SURGE PROTECTION AND FILTERING</b> |                   |                            |
| Attenuation                           | 32 dB             |                            |
| Maximum Surge Current H-N             | 800 V             |                            |
| Response Time                         | <1 Nanosecond     |                            |
| Surge Suppression (Joules)            | 500 J             |                            |

|                                   | P403URC1                  | P600WUHD          |
|-----------------------------------|---------------------------|-------------------|
| <b>PHYSICAL</b>                   |                           |                   |
| Dimensions (LxWxH) (in.)          | 3.66 x 0.72 x 11.54       | 3.75 x 0.48 x 5.5 |
| Shipping - Dimensions (WxHxD, in) | 3.5 x 15.75 x 9.5 (in)    |                   |
| Package Weight (lbs.)             | 0.6                       |                   |
| <b>CERTIFICATIONS</b>             |                           |                   |
| Environmental                     | RoHS Compliant            |                   |
| Safety                            | UL1449 3rd Edition   cUL  |                   |
| <b>WARRANTY</b>                   |                           |                   |
| Product Warranty                  | Limited Lifetime Warranty |                   |
| Connected Equipment Guarantee     | Lifetime                  |                   |
| CEG Amount                        | \$25,000                  |                   |