### **CyberPower**

# MP1087SS | ESSENTIAL SURGE PROTECTORS TWO-PACK

### Protect home and office computers, electronics, and home theater equipment

The CyberPower MP1087SS surge protector two-pack offers vital surge protection for common home and office electronics such as computers and peripherals, home theater equipment, and appliances. With 500 joules of surge protection, both units in the MP1087SS prevent power surges and power spikes caused by storms and electrical grid fluctuations from reaching and potentially harming your valuable electronic equipment. Each surge protector in the MP1087SS has six standard, grounded power outlets and a three-foot braided power cord with a standard grounded plug.

#### **TYPICAL APPLICATIONS**

- Personal Computers
- Chargers
- Personal Electronics

#### **FEATURES**

- AC Outlets: 6
- AC Outlet Type: NEMA 5-15R
- Surge Protection: 500 Joules
- · Cord Length: 3 ft
- Cord Type: Braided
- Plug Type: NEMA 5-15P
- Electrical Rating: 125V/15A/60Hz
- Connected Equipment Guarantee: \$25,000
- Warranty: Lifetime Limited Warranty



#### **SPECIFICATIONS**

| INPUT                     |                |  |
|---------------------------|----------------|--|
| Circuit Breaker           | 15 A           |  |
| Cord Length               | 3 ft (0.9 m)   |  |
| Input Plug Type           | NEMA 5-15P     |  |
| Maximum Input Current     | 15 A           |  |
| Plug Style                | Straight       |  |
| OUTPUT                    |                |  |
| Outlet Type               | 6 - NEMA 5-15R |  |
| Outlets - Total           | 6              |  |
| Output Voltage            | 125 VAC        |  |
| Output Watts - Continuous | 1,875 W        |  |

| CURAT PROTECTION AND       |                           |
|----------------------------|---------------------------|
| SURGE PROTECTION AND       | FILIERING                 |
| Attenuation                | 32 dB                     |
| Clamping Voltage           | 800V (H-N)                |
| EMI/RFI Filtration         | 150 KHz<br>100 MHz<br>Yes |
| Maximum Surge Current      | 15,000 A                  |
| Maximum Surge Current H-N  | 15,000 A                  |
| Maximum Surge Voltage      | 6,000 V                   |
| Response Time              | <1 Nanosecond             |
| Surge Suppression (Joules) | 500 J                     |
|                            |                           |

## MP1087SS ESSENTIAL SURGE PROTECTORS TWO-PACK

#### **SPECIFICATIONS - CONT.**

| PHYSICAL  |   |
|---|---|
| Color   | White   |
| Form Factors Supported                            | Keyhole (Wall Mount or<br>Under-counter Installation) |
| Material of Construction                          | Plastic   |
| DIMENSIONS  |   |
| Physical Dimensions -<br>Width/Height/Depth (cm)  | 4.72 x 3.45 x 24.77 (cm)                              |
| Physical Dimensions -<br>Width/Height/Depth (mm)  | 47 x 35 x 248 (mm)                                    |
| Physical Dimensions -<br>Width/Height/Depth (in.) | 1.86 x 1.36 x 9.75 (in)                               |
| Physical Weight (kg)                              | 0.26  |
| Physical Weight (lb)                              | 0.57  |

| SHIPPING DIMENSIONS                              |   |
|--|---|
| Shipping Dimensions -<br>Width/Height/Depth (cm) | 13.97 x 27.31 x 8.89 cm                   |
| Shipping Dimensions -<br>Width/Height/Depth (mm) | 139.7 x 273.05 x 88.9 mm                  |
| Shipping Dimensions -<br>Width/Height/Depth (in) | 5.5 x 10.75 x 3.5 in.                     |
| Shipping Weight (kg)                             | 0.57 kg                                   |
| Shipping Weight (lbs.)                           | 1.25 lbs.                                 |
| CERTIFICATIONS                                   |   |
| CERTIFICATIONS                                   |   |
| <b>CERTIFICATIONS</b> Environmental              | RoHS Compliant                            |
|  | RoHS Compliant UL1363, UL1449 4th Edition |
| Environmental                                    |   |
| Environmental Safety                             |   |
| Environmental Safety WARRANTY                    | UL1363, UL1449 4th Edition                |