



# P205UCQ | HOME OFFICE SURGE PROTECTORS

Protect home and office computers, electronics, and home theater equipment

The CyberPower P205UCQ brings you power, protection, and versatility – all in one compact unit. Featuring 2 AC power outlets with 1,500J of surge protection, 1 USB-A charging port, 1 USB-C charging port, and a 10W wireless Qi charging pad that works with iPhone and Android phones. It's perfect for desk tops, table tops or other high-traffic areas of the home or office.



### TYPICAL APPLICATIONS

- Personal Electronics
- Wireless Speakers
- Cell Phones
- Tablets

### FEATURES

- Surge suppression: 1,500 J
- Outlet type: NEMA 5-15R
- Outlet quantity: 2
- Total USB Output: 18W
- USB-C charge ports: 1
- USB-C charge output: 15W (shared)
- USB-A charge ports: 1
- USB-A charge output: 2.4A (shared)
- Wireless Charging: Qi 10W
- Power cord length: 5 ft
- Power cord type: braided
- Plug style: Right-angle 45° offset
- Volts: 125 V
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$100,000

## SPECIFICATIONS

INPUT	
Circuit Breaker	None
Cord Length	5 ft (1.5 m)
Input Plug Type	NEMA 5-15P
Input Voltage	110 - 125 VAC
Maximum Input Current	15 A
Plug Style	Right Angle - 45° Offset

OUTPUT	
Outlet Type	2 - NEMA 5-15R
Outlets - Total	2
USB Charge Port	Yes
USB Charge Port Amperage	2.4 A (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	1 Type A 1 Type C
USB Charge Port Voltage	5 VDC
USB Charge Port Watts	15 Watts
Wireless Charging	Yes
Wireless Charging Output	10 W
Wireless Charging Type	Qi Certified

# P205UCQ

## HOME OFFICE SURGE PROTECTORS

### SPECIFICATIONS CONT.

#### SURGE PROTECTION & FILTERING

Clamping Voltage	600V (H-N, H-G, N-G)
Coax Protection RG6	None
EMI/RFI Filtration	No
Maximum Surge Current	15,000 A
Maximum Surge Current H-G	N/A
Maximum Surge Current H-N	15,000 A
Maximum Surge Current N-G	N/A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	1,500 J

#### PHYSICAL

Color	White
Form Factors Supported	Horizontal Mount in Variety of Other Applications
Material of Construction	Plastic

#### PHYSICAL DIMENSIONS

Physical Dimensions - WxHxD (cm)	8.41 x 4.29 x 8.41 cm
Physical Dimensions - WxHxD (mm)	84 x 43 x 84 mm
Physical Dimensions - WxHxD (in.)	3.31 x 1.69 x 3.31 in.
Weight (kg)	0.54 kg
Weight (lb)	1.20 lbs.

#### SHIPPING DIMENSIONS

Shipping Dimensions - WxHxD (cm)	13.34 x 16.26 x 8.38 cm
Shipping Dimensions - WxHxD (mm)	133.35 x 162.56 x 83.82 mm
Shipping Dimensions - WxHxD (in)	5.25 x 6.4 x 3.3 in.
Weight (kg)	0.68 kg
Weight (lb)	1.50 lbs.

#### CERTIFICATIONS

Environmental	RoHS Compliant
Safety	UL1449 UL2738 UL1310 FCC cUL DOE VI

#### WARRANTY

CEG Amount	\$100,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited Warranty