



P2WUCHD 2 OUTLET WALL-TAP WITH USB

Wall-tap surge protector with USB charging

The P2WUCHD Wall-tap Surge Protector with USB safeguards common home and office devices, such as computers and electronics, by absorbing spikes in energy caused by storms and electrical power surges. It provides 500 joules of protection, has 2 surge-protected outlets and a wall-tap plug. One USB-A port (2.4 Amp) and one USB-C port (18W PD) charge mobile, USB enabled devices. The P2WUCHD also features EMI/RFI noise filtering, an impact-resistant casing, and an integrated device shelf on top of the unit for convenient charging and cord management.

The P2WUCHD also features metal oxide varistor (MOV) technology, an EMI/RFI noise filter, and impact-resistant casing. This surge protector wall-tap comes with a One-Year Limited Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Consumer Electronics

FEATURES

- Surge suppression: 500 J
- Volts: 125 V
- Circuit breaker: 15A
- Plug type: NEMA 5-15P
- AC Outlets: 2
- Outlet type: NEMA 5-15R
- USB-A charge ports: 1
- USB-A charge output: 2.4A
- USB-C charge ports: 1
- USB-C charge output: 18W
- EMI/RFI Filtration: Yes
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$25,000



SPECIFICATIONS

INPUT	
Cord Length	Wall-tap
Plug Style	Wall-tap
OUTPUT	
Outlet Type	2 NEMA 5-15R
Outlets - Total	2
USB Charge Port	Yes
USB Charge Port Amperage	2.4 Amps (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	1 Type A 1 Type C
USB Charge Port Voltage	5 VDC
USB Charge Port Watts	18 Watts

SURGE PROTECTION AND FILTERING	
Attenuation	32 dB
Coax Protection RG6	None
USB Charge Port	Yes
EMI/RFI Filtration	150 KHz 100 MHz
Maximum Surge Current H-N	800 A
Response Time	<1 Nanosecond
Surge Suppression (Joules)	500 J
PHYSICAL	
Color	White
Form Factor	Wall-tap
Material of Construction	Plastic

P2WUCHD

2 OUTLET WALL-TAP WITH USB

SPECIFICATIONS CONT.

DIMENSIONS

Physical Dimensions - WxHxD (cm)	6.81 x 13.89 x 3.58 cm
Physical Dimensions - WxHxD (mm)	68 x 139 x 36 mm
Physical Dimensions - WxHxD (in.)	2.68 x 5.47 x 1.41 in.
Weight (kg)	0.23 kg
Weight (lb)	0.50 lbs.

SHIPPING DIMENSIONS

Shipping Dimensions - WxHxD (cm)	6.81 x 13.89 x 3.58 cm
Shipping Dimensions - WxHxD (mm)	68.07 x 138.94 x 35.81 mm
Shipping Dimensions - WxHxD (in)	2.68 x 5.47 x 1.41 in.
Shipping Weight (kg)	0.24 kg
Shipping Weight (lbs.)	0.52 lbs.

CERTIFICATIONS

Environmental	RoHS Compliant
Safety	UL498A UL1449 UL1310 DOE VI

WARRANTY

CEG Amount	\$25,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited Warranty