



P4WSU | HOME OFFICE SURGE PROTECTION

Protect home and office computers, and electronics.

The CyberPower Home Office Surge Protector P4WSU expands a household outlet to safely and conveniently power several devices at a single location anywhere in the home. The wall-tap design and swivel outlets make it easy to accommodate up to four power cords in tight plug-in locations. The four 4.2-Amp USB charging ports also swivel for efficient cord management.

The P4WSU provides peace of mind with 900 joules of surge protection. The EMI/RFI Noise Filter limits electromagnetic and radio frequency interference to improve TV picture and sound quality. Plus, it is backed by a 1-Year Limited Warranty and a \$75,000 Connected Equipment Guarantee.



TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Consumer Electronics

FEATURES

- Surge suppression: 900 J
- Volts: 125 V
- Plug type: NEMA 5-15P
- Outlet type: 4 NEMA 5-15R
- USB charge ports: 4 (4.2-Amp)
- USB charge type: 4 USB Type A
- EMI/RFI Filtration: Yes
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$75,000

SPECIFICATIONS

INPUT	
Circuit Breaker	None
Cord Length	Wall-tap
Input Plug Type	NEMA 5-15P
Input Voltage	125 VAC
Maximum Input Current	15 A
Plug Style	Wall-tap

OUTPUT	
Outlet Type	4 NEMA 5-15R
Outlets - Total	4
USB Charge Port	Yes
USB Charge Port Amperage	4.2 Amps (Shared)
USB Charge Port Quantity	4
USB Charge Port Type	Type A
USB Charge Port Voltage	5 VDC

P4WSU

HOME OFFICE SURGE PROTECTION

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING

Attenuation	32 dB
Clamping Voltage	800V (H-N)
EMI/RFI Filtration	Yes
Maximum Surge Current	30,000 A
Maximum Surge Current H-G	N/A
Maximum Surge Current H-N	30,000 A
Maximum Surge Current N-G	N/A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	900 J

PHYSICAL

Color	White
Form Factors Supported	Direct plug
Material of Construction	Plastic

DIMENSIONS

Physical Dimensions - WxHxD (cm)	10.36 x 13.51 x 5.59 cm
Physical Dimensions - WxHxD (mm)	104 x 135 x 56 mm
Physical Dimensions - WxHxD (in.)	4.08 x 5.32 x 2.2 in.
Weight (kg)	0.26 kg
Weight (lb)	0.57 lbs.

SHIPPING DIMENSIONS

Shipping Dimensions - WxHxD (cm)	11.43 x 15.88 x 6.35 cm
Shipping Dimensions - WxHxD (mm)	114.3 x 158.75 x 63.5 mm
Shipping Dimensions - WxHxD (in)	4.5 x 6.25 x 2.5 in.
Shipping Weight (kg)	0.38 kg
Shipping Weight (lbs.)	0.83 lbs.

CERTIFICATIONS

Environmental	RoHS Compliant
Safety	UL498a UL1310 UL1449 FCC DOE VI

WARRANTY

CEG Amount	\$75,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited