



# P504UC HOME OFFICE SURGE PROTECTION

Protect home and office computers, electronics, and home theater equipment

The CyberPower Surge Protector P504UC prevents spikes in energy caused by storms and electrical power surges from reaching your home electronics such as audio/video equipment, laptops and desk top computers, household appliances and small electronics. The P504UC provides 500 joules of surge protection, 5 AC outlets, 1 USB-C charging port, 1 USB-A charging port, and a braided 4-foot power cord with a right-angle plug.

Features of the P504UC include automatic shutdown, an EMI/RFI noise filter, metal oxide varistor (MOV) technology, an On/Off switch with integrated 15-Amp circuit breaker, LED indicator, low profile plug, keyhole mounting slots, and damage-resistant construction. This surge suppressor comes with a One-Year Limited Warranty and a \$25,000 Connected Equipment Guarantee.



## TYPICAL APPLICATIONS

- Gaming Systems
- Consumer Electronics
- Chargers
- Laptop Computers

## FEATURES

- Surge suppression: 500 J
- Outlet type: NEMA 5-15R
- Outlet quantity: 5
- Total USB Output: 15W
- USB-C charge ports: 1
- USB-C charge output: 15W
- USB-A charge ports: 2
- USB charge output: 2.4A
- Power cord length: 4 ft
- Plug style: Right-angle 45° offset
- Volts: 125 V
- Circuit breaker: 15 A
- EMI/RFI Filtration: Yes
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$25,000

## SPECIFICATIONS

| INPUT                 |              |
|-----------------------|--------------|
| Circuit Breaker       | 15 A         |
| Cord Length           | 4 ft (1.2 m) |
| Input Plug Type       | NEMA 5-15P   |
| Maximum Input Current | 15 A         |
| Plug Style            | Low Profile  |

| OUTPUT                   |                      |
|--------------------------|----------------------|
| Outlet Type              | 5 - NEMA 5-15R       |
| Outlets - Total          | 5                    |
| USB Charge Port          | Yes                  |
| USB Charge Port Amperage | 2.4 Amps (Shared)    |
| USB Charge Port Quantity | 2                    |
| USB Charge Port Type     | 1 Type A<br>1 Type C |
| USB Charge Port Voltage  | 5 VDC                |
| USB Charge Port Watts    | 15 Watts             |

# P504UC

## HOME OFFICE SURGE PROTECTION

### SPECIFICATIONS CONT.

#### SURGE PROTECTION AND FILTERING

|                            |                           |
|----------------------------|---------------------------|
| Clamping Voltage           | 800V (H-N)                |
| EMI/RFI Filtration         | 150 KHz<br>100 MHz<br>Yes |
| Maximum Surge Current      | 15,000 A                  |
| Maximum Surge Current H-N  | 15,000 A                  |
| Maximum Surge Voltage      | 6,000 V                   |
| Surge Suppression (Joules) | 500 J                     |

#### PHYSICAL

|                          |  |
|--------------------------|--|
| Color                    | White  |
| Form Factors Supported   | Keyhole (Wall Mount or Under-counter Installation) |
| Material of Construction | Plastic  |

#### PHYSICAL DIMENSIONS

|                                   |                        |
|-----------------------------------|------------------------|
| Physical Dimensions - WxHxD (cm)  | 4.55 x 3.81 x 24.79 cm |
| Physical Dimensions - WxHxD (mm)  | 45 x 38 x 248 mm       |
| Physical Dimensions - WxHxD (in.) | 1.79 x 1.50 x 9.76 in. |
| Weight (kg)                       | 0.34 kg                |
| Weight (lb)                       | 0.75 lbs.              |

#### SHIPPING DIMENSIONS

|                                  |                           |
|----------------------------------|---------------------------|
| Shipping Dimensions - WxHxD (cm) | 4.55 x 7.04 x 24.69 cm    |
| Shipping Dimensions - WxHxD (mm) | 45.47 x 70.36 x 246.89 mm |
| Shipping Dimensions - WxHxD (in) | 1.79 x 2.77 x 9.72 in.    |
| Weight (kg)                      | 0.38 kg                   |
| Weight (lb)                      | 0.837 lbs.                |

#### CERTIFICATIONS

|               |  |
|---------------|--|
| Environmental | RoHS Compliant   |
| Safety        | UL1449 3rd Edition<br>UL1363<br>UL1310<br>FCC<br>cUL<br>DOE VI |

#### WARRANTY

|                               |                           |
|-------------------------------|---------------------------|
| CEG Amount                    | \$25,000                  |
| Connected Equipment Guarantee | Lifetime                  |
| Product Warranty              | One-Year Limited Warranty |