



P600WSURC1 | HOME OFFICE SURGE PROTECTION

Protect home and office computers, electronics, and home theater equipment

The CyberPower Home Office Surge Protector P600WSURC1 prevents spikes in energy caused by storms and electrical power surges from reaching your home office equipment such as laptops, small electronics, and chargers. The P600WSURC1 provides 1,200 joules of protection and 6 AC outlets with a single wall-tap plug. The two 2.4 Amp USB ports quickly charge USB-powered devices, including tablets.

Features of the P600WSURC1 include automatic shutdown, an EMI/RFI noise filter, metal oxide varistor (MOV) technology, surge protection LED indicator (*Protected*), damage-resistant housing, and an anchoring screw. This surge suppressor comes with a One-Year Limited Warranty and a \$100,000 Connected Equipment Guarantee.



TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Consumer Electronics

FEATURES

- Surge suppression: 1,200 J
- Volts: 125 V
- USB Ports: (2) 2.4 Amp
- Plug type: 3-prong
- Outlets: 6 surge-protected (standard)
- Wall-tap: Yes
- LED indicator: Yes
- EMI/RFI Filtration: Yes
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$100,000

SPECIFICATIONS

INPUT	
Circuit Breaker	None
Cord Length	Wall-tap
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Wall-tap
OUTPUT	
Outlet Type	6 NEMA 5-15R
Outlets - Total	6
USB Charge Port	Yes
USB Charge Port Amperage	2.4 Amps (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	Type A
USB Charge Port Voltage	5 VDC

SURGE PROTECTION & FILTERING - CON'T	
Attenuation	32 dB
Clamping Voltage	400V (H-N, H-G)
Coax Protection RG6	None
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	30,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	15,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	1,200 J

P600WSURC1

HOME OFFICE SURGE PROTECTION

SPECIFICATIONS CONT.

PHYSICAL	
Color	Black
Form Factors Supported	Direct plug
Material of Construction	Plastic
DIMENSIONS	
Physical Dimensions - WxHxD (cm)	10.67 x 16.26 x 6.35 cm
Physical Dimensions - WxHxD (mm)	107 x 163 x 64 mm
Physical Dimensions - WxHxD (in.)	4.2 x 6.4 x 2.5 in.
Weight (kg)	0.27 kg
Weight (lb)	0.60 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - WxHxD (cm)	10.8 x 21.03 x 7.82 cm
Shipping Dimensions - WxHxD (mm)	107.95 x 210.31 x 78.23 mm
Shipping Dimensions - WxHxD (in)	4.25 x 8.28 x 3.08 in.
Shipping Weight (kg)	0.36 kg
Shipping Weight (lbs.)	0.80 lbs.

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL498A UL1363
WARRANTY	
CEG Amount Value	\$100,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited