



P600WUCHD 6-OUTLET WALL-TAP WITH USB

Wall-tap surge protector with USB charging

The P600WUCHD Wall-tap Surge Protector with USB safeguards common home and office devices, such as computers and electronics, by absorbing spikes in energy caused by storms and electrical power surges. It provides 500 joules of protection, has 6 surge-protected outlets and a wall-tap plug. One USB-A port (2.4 Amp) and one USB-C port (15W) charge mobile, USB enabled devices. The P600WUCHD also features EMI/RFI noise filtering, an impact-resistant casing, and an integrated device shelf on top of the unit for convenient charging and cord management.

The P600WUCHD also features metal oxide varistor (MOV) technology, an EMI/RFI noise filter, and impact-resistant casing. This surge protector wall-tap comes with a One Year Limited Warranty and a Connected Equipment Guarantee.



TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Consumer Electronics

FEATURES

- Surge suppression: 500 J
- Volts: 125 V
- Circuit breaker: 15A
- Plug type: NEMA 5-15P
- AC Outlets: 6
- Outlet type: NEMA 5-15R
- USB-A charge ports: 1
- USB-A charge output: 2.4A
- USB-C charge ports: 1
- USB-C charge output: 15W
- EMI/RFI Filtration: Yes
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$25,000

SPECIFICATIONS

INPUT	
Cord Length	Wall-tap
Plug Style	Wall-tap
OUTPUT	
Outlet Type	6 NEMA 5-15R
Outlets - Total	6
USB Charge Port	Yes
USB Charge Port Amperage	2.4 Amps (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	1 Type A 1 Type C
USB Charge Port Voltage	5 VDC
USB Charge Port Watts	15 Watts

SURGE PROTECTION AND FILTERING	
Attenuation	32 dB
Coax Protection RG6	None
EMI/RFI Filtration	150 KHz 100 MHz
Maximum Surge Current H-N	800 A
Response Time	<1 Nanosecond
Surge Suppression (Joules)	500 J
PHYSICAL	
Color	White
Form Factor	Wall-tap
Material of Construction	Plastic

P600WUCHD

6-OUTLET WALL-TAP WITH USB

SPECIFICATIONS CONT.

DIMENSIONS	
Physical Dimensions - WxHxD (cm)	10.16 x 17.46 x 3.49 cm
Physical Dimensions - WxHxD (mm)	102 x 175 x 35 mm
Physical Dimensions - WxHxD (in.)	4 x 6.875 x 1.375 in.
Weight (kg)	0.27 kg
Weight (lb)	0.60 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - WxHxD (cm)	10.16 x 17.46 x 5.59 cm
Shipping Dimensions - WxHxD (mm)	101.6 x 174.63 x 55.88 mm
Shipping Dimensions - WxHxD (in)	4 x 6.875 x 2.2 in.
Shipping Weight (kg)	0.28 kg
Shipping Weight (lbs.)	0.61 lbs.

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1449 3rd Edition
WARRANTY	
CEG Amount	\$25,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited Warranty