



## PDU15BV14F Basic PDU

Engineered to distribute UPS, generator or utility AC power to equipment.

The CyberPower 14-outlet (14 Front) OU vertical rack mount basic power distribution unit (PDU15BV14F) provides 120V 15A output. It distributes power to 14 NEMA 5-15R receptacles from a single NEMA 5-15P plug, with unfiltered electrical pass-through.

Designed for datacenters and other electrically demanding applications, this unit has a rugged, industrial-grade metal housing and a 10-foot AC power cord. It supports vertical, horizontal and wall mount installation, includes a cord retention tray and is ETL/RoHS certified.

A Lifetime Warranty ensures that this PDU is free of defects in design, assembly, material and workmanship.

### Typical Applications

- Servers
- Network Devices
- Telecom Equipment

### Features

- Basic PDU
- Switch-Free Design
- Industrial-Grade Metal Housing
- Lifetime Warranty

# PDU15BV14F Basic PDU

Engineered to distribute UPS, generator or utility AC power to equipment.

| GENERAL                      |  |
|------------------------------|--|
| Type                         | Basic PDU  |
| Phase                        | Single Phase   |
| INPUT                        |  |
| Voltage                      | 120V   |
| Current                      | 15A max  |
| Frequency                    | 50Hz/60Hz  |
| Plug Type                    | NEMA 5-15P   |
| Plug Style                   | Straight   |
| Cord Length                  | 10'  |
| OUTPUT                       |  |
| Nominal Output Voltage       | 120V   |
| Outlets - Total              | 14   |
| Outlet Type                  | NEMA 5-15R   |
| Outlets - Front              | 14   |
| Outlets - Rear               | 0  |
| Overload Protection          | 15A  |
| PHYSICAL                     |  |
| Rack Size                    | 0U   |
| Form Factors Supported       | Vertical Rackmount, Wallmount                        |
| Cord Retention Organizers    | Yes  |
| External Site Ground Pin     | Yes  |
| Adjustable Mounting Brackets | 3 sets (L-short, L-long, Flat)                       |
| Dimensions (WxHxD) (in.)     | 1.75 x 24 x 1.5                                      |
| Weight (lbs.)                | 4.0  |
| ENVIRONMENTAL                |  |
| Operating Temperature        | 32°F to 95°F / 0°C to 35°C                           |
| Operating Relative Humidity  | 0% - 95% non-condensing                              |
| Storage Temperature          | 5°F to 113°F / -15°C to 45°C                         |
| Maximum Operating Elevation  | 10,000 ft / 3,000 m                                  |
| Maximum Storage Elevation    | 50,000 ft / 15,000 m                                 |
| CERTIFICATIONS               |  |
| Safety                       | UL1363 certified by ETL (USA),<br>CSA C22.2 (Canada) |
| Environmental                | RoHS Compliant                                       |
| WARRANTY                     |  |
| Product Warranty             | Lifetime   |