



## PDU20BV16F Basic PDU

Engineered to distribute UPS, generator or utility AC power to equipment.

The CyberPower 16-outlet (16 Front) OU vertical rack mount basic power distribution unit (PDU20BV16F) provides 120V 20A output. It distributes power to 16 NEMA 5-20R receptacles from a single NEMA 5-20P plug, with unfiltered electrical pass-through.

Designed for datacenters and other electrically demanding applications, this unit has a rugged, industrial-grade metal housing and a 10-foot AC power cord. It supports vertical, horizontal and wall mount installation, includes a cord retention tray and is ETL/RoHS certified.

A Lifetime Warranty ensures that this PDU is free of defects in design, assembly, material and workmanship.

### Typical Applications

- Servers
- Network Devices
- Telecom Equipment

### Features

- Basic PDU
- Switch-Free Design
- Industrial-Grade Metal Housing
- Lifetime Warranty

# PDU20BV16F Basic PDU

Engineered to distribute UPS, generator or utility AC power to equipment.

GENERAL	
Type	Basic PDU
Phase	Single Phase
INPUT	
Voltage	120V
Current	20A max
Frequency	50Hz/60Hz
Plug Type	NEMA 5-20P
Plug Style	Straight
Cord Length	10'
OUTPUT	
Nominal Output Voltage	120V
Outlets - Total	16
Outlet Type	NEMA 5-20R
Outlets - Front	16
Outlets - Rear	0
Overload Protection	20A
PHYSICAL	
Rack Size	0U
Form Factors Supported	Vertical Rackmount, Wallmount
Cord Retention Organizers	Yes
External Site Ground Pin	Yes
Adjustable Mounting Brackets	3 sets (L-short, L-long, Flat)
Dimensions (WxHxD) (in.)	1.75 x 36 x 1.5
Weight (lbs.)	6.0
ENVIRONMENTAL	
Operating Temperature	32°F to 95°F / 0°C to 35°C
Operating Relative Humidity	0% - 95% non-condensing
Storage Temperature	5°F to 113°F / -15°C to 45°C
Maximum Operating Elevation	10,000 ft / 3,000 m
Maximum Storage Elevation	50,000 ft / 15,000 m
CERTIFICATIONS	
Safety	UL1363 certified by ETL (USA), CSA C22.2 (Canada)
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	Lifetime