



# PR750LCDN SMART APP SINEWAVE UPS

Offers significant energy savings, battery backup and surge protection.

A mini-tower UPS with line interactive topology, the CyberPower Smart App Sinewave PR750LCDN provides battery backup, power protection (using sine wave output), and surge protection for corporate servers, department servers, storage appliances, network devices, and telecom installations requiring Active PFC power source compatibility.

The PR750LCDN features a pre-installed remote management card RMCARD205, which provides remote management and configuration of the UPS via a standard web browser or network management system.

The PR750LCDN comes with a three-year warranty (including coverage of batteries) and a Connected Equipment Guarantee.



## TYPICAL APPLICATIONS

- Data Center Servers
- Network and Storage Devices
- Complex Security Systems
- PBX and VoIP Installations

## FEATURES

- 750VA / 525W
- Line Interactive Topology
- Active PFC Compatible
- ENERGY STAR® Qualified
- Extendable LCD Control Panel
- SNMP/HTTP Remote Management
- Full-time Surge Protection and Battery Backup
- Mini-Tower Form Factor
- 6 Outlets / USB / Serial / EPO Port
- PowerPanel® Business
- 3-Year Warranty

## SPECIFICATIONS

GENERAL	
UPS Topology	Line Interactive
Energy Saving	GreenPower UPS™ Bypass Technology
ENERGY STAR® Qualified	Yes

INPUT	
Voltage	120V
Voltage Range	75Vac - 154Vac
Frequency	47Hz - 63Hz (auto-sensing)

# PR750LCDN SMART APP SINEWAVE UPS

## SPECIFICATIONS - CONT.

### INPUT - CONT.

Plug Type	NEMA 5-15P
Plug Style	Straight
Cord Length	6'

### OUTPUT

VA	750
Watts	525
On Battery Voltage	120Vac $\pm$ 5%
On Battery Frequency	50/60Hz $\pm$ 1%
Automatic Voltage Regulation (line mode)	Yes
On Battery Waveform	Sine Wave
Outlets - Total	6
Outlet Type	NEMA 5-15R
Outlets - Battery & Surge Protected	6
Overload Protection	Internal circuitry limiting / circuit breaker
Transfer Time	4ms - 8ms

### BATTERY

Runtime at Half Load (min)	15
Runtime at Full Load (min)	3
Battery Type	Sealed Lead-Acid
Battery Size	12V/7AH
Hot-Swappable	Yes
Replacement Battery	RB1270X2B
Battery Quantity	2
User Replaceable	Yes
Typical Recharge Time	3 Hours - Quick Charge Mode, 8 Hours - Eco Mode

### SURGE PROTECTION & FILTERING

Surge Suppression	1,030 Joules
EMI/RFI Filtration	Yes

### MANAGEMENT & COMMUNICATIONS

LCD Control Panel	41 different settings or status options via the UPS Status menu, UPS Setup & Control menus, and run Testing/Battery Calibration menus.
Extendable LCD Control Panel	Yes - Standard with 4.5 ft. Cable
HID Compliant USB Port	Yes
Serial Port	Yes
EPO Port	Yes
Management Cable	USB Cable, Serial Cable, EPO Cable
LED Indicators	Power On, On-Line, On-Battery, Wiring fault, Replace Battery
Audible Alarms	On Battery, Low Battery, Overload, Fault
Software	PowerPanel® Business Edition
SNMP / HTTP Remote Monitoring	Yes, with pre-installed RMCARD205

### PHYSICAL

Form Factor	Mini-Tower
Dimensions (WxHxD) (in.)	5.4 x 6.4 x 13.7
Weight (lbs.)	27.0

### ENVIRONMENTAL

Operating Temperature	32°F to 104°F / 0°C to 40°C
Operating Relative Humidity	0% - 90% non-condensing

### CERTIFICATIONS

Safety	FCC DOC Class A
Environmental	RoHS Compliant

### WARRANTY

Product Warranty	3 Years Limited
Connected Equipment Guarantee	Lifetime
CEG Amount	\$375,000