



RB1260X8 REPLACEMENT BATTERY CARTRIDGE



Restore life to your UPS system

The RB1260X8 UPS Replacement Battery Cartridge restores life to CyberPower UPS systems that have weak or completely depleted internal batteries. The RB1260X8 contains eight 12V/6Ah batteries, certified to meet or exceed original manufacturer specifications. This leak-proof, sealed lead-acid battery never requires replacement fluid. The pre-assembled cartridge installs easily into your CyberPower UPS system and is shipped with reusable packaging for delivering expired batteries to a suitable recycling center. The RB1260X8 comes with instructions, recycling information, and an eighteen-month warranty.

FEATURES

- Number of batteries: 8
- Battery size: 12V / 6AH
- Battery type: Sealed lead-acid
- Dimensions - Width x Height x Depth: 7.9 x 2.8 x 17.9 in.
- Weight: 34.8 lbs
- User-Replaceable: Yes
- Warranty: 18-month

ELIGIBLE MODELS

PR2200RTXL2UAN	PR2200RTXL2UHVAN
PR2200RTXL2UACN	PR3000RTXL2UHVAN
PR3000RTXL2UAN	BP48VP2U03
PR3000RTXL2UACN	BP48VP2U04

SPECIFICATIONS

BATTERY	
Battery Quantity	8
Battery Size	12 V / 6 Ah
Battery Type	Sealed Lead-Acid Battery
ENVIRONMENTAL	
Operating Elevation	0 ft - 9,843 ft (0 to 3,000 m)
Operating Relative Humidity	0% - 95% non-condensing
Operating Temperature	32 °F - 104 °F (0 °C - 40 °C)
Storage Elevation	0 ft - 49,213 ft (0 m - 14,999 m)
Storage Relative Humidity	0% - 95% non-condensing
Storage Temperature	5 °F - 113 °F (-15 °C - 45 °C)

PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	20.07 x 7.11 x 45.47 cm
Physical Dimensions - Width/Height/Depth (mm)	201 x 71 x 455 mm
Physical Dimensions - Width/Height/Depth (in.)	7.9 x 2.8 x 17.9 in.
Weight (kg)	15.79 kg
Weight (lb)	34.8 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	26.67 x 15.24 x 53.34 cm
Shipping Dimensions - Width/Height/Depth (mm)	266.7 x 152.4 x 533.4 mm
Shipping Dimensions - Width/Height/Depth (in.)	10.5 x 6 x 21 in.
Weight (kg)	16.6 kg
Weight (lb)	36.6 lbs.
WARRANTY	
Product Warranty	18-month Limited