

# CyberPower

## RELAYIO500 LOCAL MANAGEMENT CARD

Offers users a solution for UPS status *monitoring* and local device control



CyberPower's RELAYIO500 is a local management solution that provides users the ability to monitor UPS status and events via 5 contact closure outputs. Easy to install in any compatible CyberPower Smart App UPS with expansion slot.

Input contact closure allows the UPS to be shutdown remotely while on Battery Mode to preserve battery power in the event of a prolonged power outage.

A Three-Year Warranty ensures that this network management card has passed our highest quality standards in design, assembly, material and workmanship.

### FEATURES

- Relay I/O Card for UPS status monitoring
- 5 relay output contact closures indicating UPS status info
- 1 relay input contact closure to shutdown UPS on Battery Mode
- Connections via DB9 port
- Hot-swappable (Plug-n-Play)

### COMPATIBILITY

- OR Series UPS systems
- PR Series UPS systems
- OL1000RTXL2U, OL1500RTXL2U, OL1500RTXL2UN, OL2200RTXL2U, OL3000RTXL2U and OL3000RTXL2UHV

## SPECIFICATIONS

### GENERAL

Type	Relay I/O UPS Monitoring Card
Contact Closure Outputs	5
Input Signal Contact	1 - UPS shutdown in Battery Mode
Output Relay Rating (Max.)	30VCD/125VAC, 3A (per relay)
External S/D Voltage	7.5V to 12V

### PHYSICAL

Dimensions (WxHxD) (in.)	1.65 x 0.6 x 3.2
Dimensions (WxHxD) (mm.)	41.8 x 14.2 x 81
Weight (lbs.)	0.11
Weight (kg.)	0.052

### SHIPPING DIMENSIONS

Dimensions (WXHXD) (in.)	6.6 x 2.3 x 6.4
Dimensions (WxHxD) (mm.)	168 x 58 x 162
Weight (lbs.)	0.35
Weight (lbs.)	0.16

### ENVIRONMENTAL

Operating Temperature	32°F to 104°F / 0°C to 40°C
Operating Humidity	0% - 95% non-condensing
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	14°F to 122°F / -10°C to 50°C
Storage Relative Humidity	0% - 95% non condensing
Storage Elevation	0-50000 feet (0-15000 meters)

### COMPATIBILITY

UPS Models	OR PR series and select OL series models, see compatibility chart for details
------------	---

### CERTIFICATIONS

Environmental	RoHS compliant
---------------	----------------

### WARRANTY

Product Warranty	3 years limited
Extended Warranty	WEXT5YR-ACC1A