CyberPower



RELAYIO600 Local Management Card Offers users a solution for UPS status monitoring and local device control

The CyberPower RELAYIO600 is a local management solution that provides users the ability to monitor UPS status and events via 5 contact closure outputs. Easy to install in any Smart App Online Series UPS system.

Input contact closure allows the UPS to be shutdown remotely while on Battery Mode to preserver battery power in the event of a prolonged power outage.

A Three-Year Warranty ensures that this network management card has passed our highest quality standards in design, assembly, material and workmanship.

Features

- Relay I/O Card for UPS status monitoring
- 5 relay output contact closures indicating UPS status information
- 1 relay input contact closure to shutdown UPS on Battery Mode
- Connections via DB9 port or Internal Terminal Block
- Hot-swappable (Plug-n-Play)

RELAYIO600 Local Management Card Offers users a solution for UPS status monitoring and local device control

GENERAL	
Туре	Relay I/O Card
PHYSICAL	
Dimensions (WxHxD) (in.)	2.64 x 1.7 x 6.13
Dimensions (WxHxD) (mm.)	67 x 43 x 155.7
Weight (oz.)	3.13
Weight (kg.)	88.6
SHIPPING DIMENSIONS	
Dimensions (WxHxD) (in.)	6.7 x 6.5 x 2.4
Dimensions (WxHxD) (mm.)	170 x 165 x 60
Weight (lbs.)	0.42
Weight (kg.)	0.192
ENVIRONMENTAL	
Operating Temperature	32°F to 104°F / 0°C to 40°C
Operating Humidity	0% - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
COMPATIBILITY	
UPS Models	*Smart App Online Series UPS
CERTIFICATIONS	
Safety	FCC, CE
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	3 Years Limited