

CyberPower



SE450G Battery Backup

Offers significant energy savings, battery backup and surge protection.

The CyberPower SE450G uninterruptible power supply (UPS) safeguards a home office PC and other electronics (monitors, printers, scanners, speakers, fax machines, CD/DVD players and iPods) from surges, spikes, sags, brownouts and other power abnormalities. Its composite integrated circuitry offers advanced lightning protection.

This UPS system utilizes GreenPower UPS™ high-efficiency design to save on energy costs by reducing energy consumption and heat buildup.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material or workmanship and further protection is offered by a \$500,000 Connected Equipment Guarantee.

Typical Applications

- Desktop Computers
- Personal Electronics

Features

- 450VA / 260W
- 8 Standard Outlets
- Standby Topology
- GreenPower UPS™
- Full-time Surge Protection and Battery Backup
- RJ11 Protection (1-in / 2 Out)
- 3-Year Warranty

SE450G Battery Backup

Offers significant energy savings, battery backup and surge protection.

GENERAL	
UPS Topology	Standby
Energy Saving	GreenPower UPS™ High Efficiency
INPUT	
Voltage	96Vac - 140Vac
Frequency	50Hz/60Hz ± 3Hz
Circuit Breaker	10 Amp
Plug Type	NEMA 5-15P
Plug Style	Right Angle, 45° Offset Right
Cord Length	5'
OUTPUT	
VA	450
Watts	260
On Battery Voltage	120Vac ± 5%
On Battery Frequency	50/60Hz ± 1%
On Battery Waveform	Simulated Sine Wave
Outlets - Total	8
Outlet Type	NEMA 5-15R
Outlets - Battery & Surge Protected	4
Outlets - Surge-Only Protected	4
Outlets - Widely Spaced	4
Overload Protection	Internal circuitry limiting / circuit breaker
BATTERY	
Runtime at Half Load (min)	7
Runtime at Full Load (min)	2
Battery Type	Sealed Lead-Acid
Battery Size	12V/3.6AH
Battery Quantity	1
User Replaceable	No
Typical Recharge Time	8 Hours
SURGE PROTECTION & FILTERING	
Surge Suppression	890 Joules
Phone Protection RJ11	1-In, 2-Out
EMI/RFI Filtration	Yes

MANAGEMENT & COMMUNICATIONS	
LED Indicators	Power On, Wiring Fault
Audible Alarms	On Battery, Low Battery, Overload, Fault
PHYSICAL	
Dimensions (WxHxD) (in.)	9.75 x 6 x 3
Weight (lbs.)	4.0
Weight (kg.)	1.8
ENVIRONMENTAL	
Operating Temperature	32 °F to 104 °F / 0 °C to 40 °C
Operating Humidity	0% - 90% non-condensing
CERTIFICATIONS	
Safety	UL1778, cUL, FCC DOC Class B, CEC
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	3 Years Limited
Connected Equipment Guarantee	Lifetime
CEG Amount	\$75,000