



## XC625 BATTERY BACKUP UPS

Offers significant energy savings,  
battery backup and surge protection.

The CyberPower XC625 uninterruptible power supply (UPS) system provides battery backup and surge protection for lightning-induced surges and other power events that can damage electronic equipment. This unit delivers battery backup to power connected electronics during a utility power failure and enough runtime to perform a graceful shutdown to protect against the loss of data and damage to valuable electronics during longer outages.

This unit is designed to minimize noise for a quieter work environment and to run efficiently to reduce power consumption. Including a sleek design, this UPS is perfect for all your home office and entertainment needs, including computers, gaming consoles, and broadband routers.

With a \$100,000 lifetime connected equipment guarantee and a three-year warranty, you can trust CyberPower's commitment to the quality of the XC625.



### TYPICAL APPLICATIONS

- Desktop Computers
- Home Networking
- Home Theater Equipment
- Personal Electronics
- Routers & Modems
- VoIP Phone Systems
- Workstations

### FEATURES

- Capacity: 625VA/375W
- Topology: Standby
- Waveform: Simulated Sine Wave
- Output: 120Vac +/- 5%
- Runtime (half/full): 9 minutes/2 minutes
- Plug type & cord: NEMA 5-15P, 5 ft. cord
- Outlets: 8 (4 surge only, 4 surge + battery backup)
- Outlet types: 8 x NEMA 5-15R
- Communication: USB
- Management software: PowerPanel®Personal
- ENERGY STAR® certified: Yes
- Warranty: Three-Year
- Connected Equipment Guarantee: \$100,000

XC625

BATTERY BACKUP UPS

SPECIFICATIONS

GENERAL	
Energy Saving	GreenPower UPS™ High-Efficiency
ENERGY STAR® certified	Yes
UPS Topology	Standby
INPUT	
Circuit Breaker	15 A
Cord Length	5 ft (1.5 m)
Input Frequency Range	47 Hz - 63 Hz
Input Plug Type	NEMA 5-15P
Nominal Input Voltage	120 VAC
OUTPUT	
On Battery Frequency	50/60 Hz +/- 1%
On Battery Voltage	120 VAC +/- 5%
On Battery Waveform	Simulated Sine Wave
Outlet Type	8 x NEMA 5-15R
Outlets - Battery & Surge Protected	4
Outlets - Surge-Only Protected	4
Outlets - Widely-Spaced	4
Outlets - Total	8
Output Power Factor	0.6
Overload Protection	Internal Circuitry Limiting Circuit Breaker Protected
Typical Transfer Time	8 ms
VA	625 VA
Watts	375 W

BATTERY	
Battery Quantity	1
Battery Size	12 Volts / 5.5 Ah
Battery Type	Sealed Lead-Acid Battery
Runtime at Full Load	2 minutes
Runtime at Half Load	9 minutes
Typical Recharge Time	8 Hours
SURGE PROTECTION & FILTERING	
EMI/RFI Filtration	Yes
Surge Suppression	890 J
MANAGEMENT & COMMUNICATIONS	
Audible Alarms	Battery Mode Low Battery Overload Fault
HID Compliant USB Port	Yes
LED Indicators	Power On
Management Cable	USB Cable
Software (Free Download)	PowerPanel® Business
PHYSICAL	
Color	Black
Form Factor	Compact
Keyhole Mounting Slots	Yes
Material of Construction	Plastic

XC625

BATTERY BACKUP UPS

SPECIFICATIONS CONT.

PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	24.89 x 14.73 x 8.13 cm
Physical Dimensions - Width/Height/Depth (mm)	249 x 147 x 81 mm
Physical Dimensions - Width/Height/Depth (in.)	9.8 x 5.8 x 3.2 in.
Weight (kg)	2.27 kg
Weight (lb)	5 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	11.43 x 20.32 x 36.83 cm
Shipping Dimensions - Width/Height/Depth (mm)	114.3 x 203.2 x 368.3 mm
Shipping Dimensions - Width/Height/Depth (in)	4.5 x 8.0 x 14.5 in.
Weight (kg)	7.48 kg
Weight (lb)	16.5 lbs.

ENVIRONMENTAL	
Operating Elevation	0 - 10,000 ft (0 - 3,048 m)
Operating Relative Humidity	0 to 95% (non-condensing)
Operating Temperature	32 to 104 °F (0 to 40 °C)
Storage Elevation	0 - 50,000 ft (0 - 15,239 m)
Storage Temperature	5 to 113 °F (-15 to -45 °C)
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1778 cUL FCC DOC Class B CEC
WARRANTY	
CEG Amount	\$100,000
Connected Equipment Guarantee	Lifetime
Extended Warranty Option	WEXT5YR-U1A
Product Warranty	3-Year Limited Warranty